

# Antenna - FL LCX CABLE 5 E - 2702860

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The leaky wave cable is a "wireless cable" which acts as an antenna and emits along its entire length. The range is limited. Track-guided systems, for example, can therefore be supplied as required, even under difficult conditions. Suitable for the 5 GHz band.

The figure shows a version of the product



## Key Commercial Data

Packing unit	1 pc
--------------	------

## Technical data

### Dimensions

Diameter	15.5 mm
----------	---------

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-70 °C ... 85 °C

### General

With connecting cable	yes
Frequency range	5 GHz
Cable resistance	1.48 Ω/km (DC inner conductor)
	2.8 Ω/km (DC phase conductor)
Gain	0 dBi
Connection method	open end
Cable weight	232.00 g/m
Smallest bending radius, fixed installation	min. 200 mm (One-time bending)
Cable, attenuation	19.1 dB/100 m, longitudinal loss (5.2 GHz)
	71 dB, coupling attenuation 95 % (5.2 GHz)
Material	Al Cu wire (inner conductors)
	Copper film (Phase conductors)
	PE foam (Insulation)
Mounting type	Wall mounting

## Antenna - FL LCX CABLE 5 E - 2702860

### Technical data

#### General

Assembly instructions	Recommended clamp distance 0.5 m
-----------------------	----------------------------------

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>