



Contact Layout

**48**



4#8 Power

| 21-48 |       |       |
|-------|-------|-------|
| Ctc   | X     | Y     |
| A     | 4.57  | 4.57  |
| B     | 4.57  | -4.57 |
| C     | -4.57 | -4.57 |
| D     | -4.57 | 4.57  |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D521S48SB**

|                |                                       |                            |   |
|----------------|---------------------------------------|----------------------------|---|
| A              | 08-10-2016                            | First Release              |   |
| ISS            | DATE                                  | Latest modification - by   | MOD N°  |
| Designed By:   |                                       | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Plug 8D series</b> |                            |   |
| SCALE          |                                       | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                       | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D521S48SB-C</b>    |                            | SHEET<br>2/2  |