

Mounting base housing - HSC-LR 3U KIT 2003 - 2201797

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail housing, 3U, Lock and Release system, width: 16.1 mm

Your advantages

- Item is from the ME-IO product range
- Tool-free mounting
- Push-in front connection technology
- Available for up to 18-pos. front connection technology

Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 046356 911580
GTIN	4046356911580

Technical data

Item properties

Brief article description	Mounting base housing
Type	HSC-LR 3U KIT 2003
Order No.	2201797
Housing type	DIN rail housing
Type	3U
Mounting type	Snap in

Dimensions

Width [w]	16.1 mm
Height [h]	45.95 mm
Depth [d]	8.8 mm

Mounting base housing - HSC-LR 3U KIT 2003 - 2201797

Technical data

Material data

Color (RAL)	orange
Flammability rating according to UL 94	V0
Housing material	Polyamide

Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport)	80 %

PCB data

Mounting position	Vertical (horizontal DIN rail)
-------------------	--------------------------------

Packaging information

Pieces per package	10
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals


Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	---	---	---------------

EAC		B.01742
-----	---	---------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>