


# R73MI2100SE00K

## Aliases (73MI2100SE00K)

R73, Film, Film/Foil Polypropylene, Automotive Grade, 0.01 uF, 10%, 400 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

### Dimensions

L 18mm +0.3/-0.5mm

H 11mm +0.1/-0.5mm

### Dimensions

T 5mm +0.2/-0.5mm  
S 15mm +/-0.4mm  
LL 4mm +2mm  
F 0.8mm +/-0.05mm

### Packaging Specifications

Packaging Bulk, Bag  
Packaging Quantity 2000

### General Information

Series R73  
Dielectric Film/Foil Polypropylene  
Style Radial  
Features Automotive Grade, Pulse  
RoHS Yes  
Lead Cut  
Qualifications AEC-Q200  
AEC-Q200 Yes  
Miscellaneous Above 85C DC And AC Voltage Derating Is 1.25%/C.

### Specifications

Capacitance 0.01 uF  
Capacitance Tolerance 10%  
Voltage AC 160 VAC  
Voltage DC 400 VDC  
Temperature Range -55/+105°C  
Rated Temperature 85°C  
Dissipation Factor 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz  
Insulation Resistance 100 GOhms  
Max dV/dt 6000 V/us  
Inductance 10 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - 6bdae993-9cce-4657-89ff-1480b5ec0e8d  
© 2006 - 2023 KEMET  
Generated 5/18/2023 - 6bdae993-9cce-4657-89ff-1480b5ec0e8d  
© 2006 - 2023 KEMET