


## F871BP124K330Z

F871, Film, Metallized Polypropylene, Safety, 0.12 uF, 10%, 330 VAC (X1), 800 VDC, 110°C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	
L	18mm -0.5mm
н	14.5mm -0.5mm
т	8.5mm -0.5mm
S	15mm +/-0.4mm
LL	4mm +2mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

## Packaging Specifications Packaging

Packaging	Pizza, Box
Packaging Quantity	663

General Information	
Series	F871
Dielectric	Metallized Polypropylene
Style	Radial
Features	MKP EMI Safety
RoHS	Yes
Lead	Cut/Short
Safety Class	X1
Qualifications	ENEC, UL, cUL, CQC
AEC-Q200	No
THB Performance	No
Component Weight	3.434 g
Miscellaneous	ClimCat: 40/110/56/B.
Shelf Life	104 Weeks

Specifications				
Capacitance	0.12 uF			
Capacitance Tolerance	10%			
Voltage AC	330 VAC (X1)			
Voltage DC	800 VDC			
Temperature Range	-40/+110°C			
Rated Temperature	110°C			
Dissipation Factor	0.2% 1kHz			
Insulation Resistance	30 GOhms			
Max dV/dt	400 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.