

Specification Sheet

Part Number: T120L9K2



Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 1000/pkg

| | |
|---------------------|---|
| Article Number | 111-12419 |
| Type | T120L |
| Color | Natural (NA) |
| Features & Benefits | <ul style="list-style-type: none">•Engineered and manufactured for maximum performance and quality.•Made from 100% high-quality plastic to ensure efficient recycling.•Inside serration for a strong grip onto bundles.•Easy application either manually or with a tensioning tool.•Bent tail allows for simpler insertion. |
| Quantity Per | bag |

Product Description

Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|---|
| Short Description | Heavy Duty Cable Tie, 30" Long, UL Rated, 120lb Tensile Strength, PA66, Natural, 1000/pkg |
| Global Part Name | T120L-PA66-NA |
| Minimum Tensile Strength (Imperial) | 120.0 |
| Minimum Tensile Strength (Metric) | 535.0 |
| Length L (Imperial) | 30.0 |
| Length L (Metric) | 760.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.30 |
| Width W (Metric) | 7.6 |
| Bundle Diameter Min (Imperial) | 0.20 |
| Bundle Diameter Min (Metric) | 5.0 |
| Bundle Diameter Max (Imperial) | 8.85 |
| Bundle Diameter Max (Metric) | 224.8 |

| | |
|-------------------------------|-------|
| Thickness T (Imperial) | 0.075 |
|-------------------------------|-------|

Thickness T (Metric) 1.9

| | |
|-----------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

Material Shortcut PA66

| | |
|--------------------|-------------|
| US MIL SPEC | SAE-AS33671 |
|--------------------|-------------|

MS3367-6-9

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ.E64139 CAGE Code 53421

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

UL Listed (US)

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

50

Customs Number

3926909988

Weight (Metric)

11.5