

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.54 mm (.100") Center Spacing Flat Cable - IDC Transition Dip Plug of system CA23	SPEC.NO.: SPCA007E
REVISIONS	ECNT120076		PAGE: 1/3

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202 Methods for test of connectors for electronic equipment
MIL - STD - 1344 Test methods for electrical connectors

3. APPLICABLE SERIES NO.: **CA23 Series**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. APPLICABLE CABLES

1.27 mm (.050") center spacing Flat Cable

Insulator O.D.: 0.85 mm dia.

Construction: AWG #28 (7/0.127 mm)

7. ACCOMMODATED P.C. BOARD

1.6 mm (.063")

REVIEWED : Eisley APPROVED : Eisley VERIFIED : Michelle .

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.54 mm (.100") Center Spacing Flat Cable - IDC Transition Dip Plug of system CA23	SPEC.NO.: SPCA007E
REVISIONS	ECNT120076		PAGE: 2/3

8. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	
8.1	Rated current and voltage		1 A 250V AC (r.m.s.)
8.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 30 mΩ
8.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
8.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Heat aging	105 ± 2°C , 96 hours	No damage
9.2	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 8-3
9.3	Temperature cycling	One cycle consists of : (1) -55 ⁺⁰ ₋₃ °C , 30 min. (2) Room temp. 10-15 min. (3) 85 ⁺³ ₋₀ °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial

ENGINEERING DEPT.		PRODUCT SPECIFICATION For 2.54 mm (.100") Center Spacing Flat Cable - IDC Transition Dip Plug of system CA23	SPEC.NO.: SPCA007E
REVISIONS	ECNT120076		PAGE: 3/3

	ITEM	TEST CONDITION	REQUIREMENT
9.4	Salt spray	Temperature: $35 \pm 3^{\circ}\text{C}$ Solution: $5 \pm 1\%$ Spray time: 48 ± 4 hours (Stamping before plated) Spray time: 24 ± 4 hours (Stamping after plated) Mate connectors and expose to the following salt mist conditions. Upon completion of the exposure period, salt deposits shall be removed by a gentle wash or dip in running water and dried naturally, after which the specified measurements shall be performed. The specimens shall be suspended from the top using waxed twine, string or nylon thread. The test only define the plating area, without plating area (as copper cross section) will not be defined. (EIA 364-26B / MIL-STD-202 Method 101)	Appearance: No damage Contact resistance: Less than twice of initial
9.5	Solder ability	Soldering time: 3 ± 0.5 second Soldering pot: $245 \pm 5^{\circ}\text{C}$	Minimum: 90% of immersed area

10. AMBIENT TEMPERATURE RANGE: -40 to + 105°C