

Quality Products. Service Excellence.

## Mounting Rack Rail Swing Frame 1418SWF Series

For use with the 1418FS and HN4FS Series












- Formed from 10 gauge steel, frames are drilled and tapped to EIA requirements for mounting standard 19" rack accessories.
- Designed for installation in 72" and 90" high enclosures. The swing frame pivots on 0.5" pins within the enclosure for easy access to the rear of rack mounted equipment.
- The frame positions at any depth within the enclosure and is fastened in the closed position with quarter turn fasteners.
- Swing frames may be mounted in 30" and 36" wide enclosures, or in 60" and 72" wide enclosures with an optional center panel support.
- One or two frames may be mounted in 30" and 36" wide enclosures with dual access, and 1,2,3 or 4 frames may be mounted in 60" and 72" wide dual access enclosures.
- · Finished in black.
- TAA compliant for GSA Schedule purchases.
- · RoHS Compliant.
- · Manufactured in North America.

## **Accessories**

· Mounting Hardware



Part No.	А	В	С	Rack Units	Enclosure Height	Width Single Door
1418SFYY	78.50	31.80	12.14	44	90.00	36.00

				Rack	Enclosure	Width
Part No.	Α	В	С	Units	Height	Single Door
1418SFY	60.50	31.80	12.14	33	72.00	36.00
1418SFX	60.50	25.82	6.14	33	72.00	30.00

Data subject to change without notice

 $\ensuremath{\text{@}}$  2021. Hammond Manufacturing Ltd. All rights reserved.