


ESD-R-25D Aliases (UECESDR25D0000) KEMET, ESD-R, EMI Cores, Noise Suppression



General Information		
Series	ESD-R	
Style	Round - Toroidal	
Cable Type	Round Cable	
Description	EMI Core Solid, For Round Cables, Toroidal Cores With Case	
RoHS	Yes	
Qualifications	UL94 V-2	
Case Color	Black	
Toroidal	ESD-R-25SD	
Materials	Ni-Zn	

Specifications	
Temperature Range	-25/+85°C
Effective Frequency	300 MHz (FM Band Range)

Click here for the 3D model.

Dimensions	
D	26mm +/-1.0mm
D2	14mm +/-1.0mm
т	15mm +/-1.0mm

Packaging Specifications	
Packaging	Tray, Box
Packaging Quantity	300
Component Weight	20.4 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.