т Ф Т	m	D	0		
Z Z D D D D D D D D D D D D D					
			LAYOUT SHOWN AS EXA	MPLE	
Ke	ying Shown as example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal				
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS25 MaxZ31 MaxVV THREADM15x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed	
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D511F2	22SC	
-Temperature Range : -65°C to +200°C		A 15-10-2016	First Release		
-Salt Spray : 48 hours					
Mass : 16.89 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	Aluminiu	um Plug 8D series	
		SCALE	General linear	NPRDS / PROJECT	
BASIC SERIES: 8D 5 - 11 F 22 SHELL TYPE : Plug with RFI Shielding	S C	NA -	Tolerances:	859	
		-		This document is the pr	operty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)			J WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission		
PLATING : F = Nickel	CONTACT TYPE : SOCKET(SOU Mattings)	-	SOURIAU		SHEET
		- A3	8D511F22		1/2
					1 1/2

-	Ξ	۵	ار (m	D	0		
4	(Contact Layout 22*						
	Ctc A B C	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905						
ω.	D	-1.905 1.905						
	_					SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommend)		
N						PN: {	Coun FR 8D511	
					ISS DATE Designed By:	L6 First Release Latest modification - by Date:		
-					SCALE NA		Alumi neral linear olerances: ±	
					FORMAT		JRIAU. DURIAU	

G

Н

F

Е

A3

D

С

