



**PARTS SPECIFICATIONS:**

1. VOLTAGE RATING: 250V
2. CURRENT RATING: 13A
3. OPERATING TEMPERATURE: -40°C to 180°C
4. INGRESS PROTECTION: IP68
5. NUMBER OF POSITIONS: 6
6. NUMBER OF ROWS: 2
7. CONTACT  
TYPE: MALE PIN  
PITCH - MATING: 0.175" (4.4mm)  
LENGTH-POST: 0.120" (3.05mm)  
FINISH-MATING: TIN  
FINISH-POST: TIN
8. INSULATION  
HEIGHT: 0.880" (22.35mm)  
MATERIAL: LCP  
COLOR: CHARCOAL BLACK
9. MATERIAL FLAMMABILITY RATING: 94V-0
10. 0.077 [2.0 mm] REF. HOLE ARE FOR SIZE #2 SCREWS.
11. PACKAGE: BULK, AND 250PC BAG
12. REFLOW OVEN CAPABLE: 240°C PEAK, 10 SEC MAX

<p><b>PROPRIETARY AND CONFIDENTIAL</b> This document and the information contained within is the property of Diversified Power International (DPI), LLC and contains Confidential and Proprietary Information which may not be reproduced in any form and may not be disclosed to any third party; and may not be used for any purpose that is contrary to it's intended purpose and use without the express written consent of DPI.</p>	<p>TOLERANCES (UNLESS NOTED): INCHES [millimeters]: 3 PLACES: ± .005 [.13 mm] 2 PLACES: ± .02 [.5 mm] ANGULAR: ± 1/2°</p>	<p>SIGNATURES</p>	<p>DATE</p>	<p>TITLE <b>PCB R/A MNT AUTOMOTIVE, 6CCT</b></p>		
	<p>THIRD ANGLE PROJECTION</p>	<p>DRAWN: NGB</p>	<p>2/14/2023</p>	<p>DIVERSIFIED POWER INTERNATIONAL, LLC 414 CENTURY COURT PINEY FLATS, TN 37686 PHONE: 423-538-9002</p>		
		<p>CHECKED: TDT</p>	<p>2/14/2023</p>			
	<p>CAD DRAWING: DO NOT SCALE</p>	<p>APPROVED: TDT</p>	<p>2/14/2023</p>	<p>NEXT ASSY: N/A</p>	<p>SIZE <b>A</b></p>	<p>DWG NO <b>AS18-DTF13-6PS</b></p>
<p>SHEET 1 OF 1</p>			<p>USED ON: N/A</p>		<p>REV</p>	