

# Flat-ribbon conductor - VS-ASI-FC-PUR-YE/1000 - 1404841


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



AS-Interface PUR flat-ribbon conductor in yellow, 2 x 1.5 mm<sup>2</sup>, 1000 m on a disposable drum



## Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 327572
GTIN	4046356327572

## Technical data

### Mechanical characteristics

Number of positions	2
Shielded	no
Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm <sup>2</sup>
Duty cycle testing	suitable for drag chain
Length of cable	1000 m

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (fixed routing)
	-30 °C ... 85 °C (Flexibly installed)
Ambient temperature (assembly)	-30 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Material data

Outer sheath, material	PUR
External sheath, color	yellow
Height	4 mm

### Electrical characteristics

# Flat-ribbon conductor - VS-ASI-FC-PUR-YE/1000 - 1404841

## Technical data

### Electrical characteristics

Rated voltage (III/3)	300 V
Rated surge voltage	2 kV

### Standards and Regulations

Duty cycle testing	suitable for drag chain
--------------------	-------------------------

### Line characteristics

Type of cable	Flat-ribbon conductor
Cable structure	2x 1.5 mm <sup>2</sup>
Conductor cross section	1.5 mm <sup>2</sup>
AWG signal line	16
Conductor structure signal line	84x 0.15 mm
Core diameter including insulation	2.5 mm
Thickness, insulation	approx. 0.5 mm
Wire colors	brown, blue
External sheath, color	lemon yellow RAL 1012
Insulation resistance	≥ 1 MΩ*km
Conductor resistance	≤ 13.7 Ω/km
Nominal voltage, cable	300 V
Test voltage, cable	2000 V
Outer sheath, material	PUR
Material conductor insulation	PP
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Smallest bending radius, fixed installation	≥ 6 mm (one-time)
Traversing direction	horizontal, above the broadside
Max. bending cycles	8000000
Bending radius	75 mm
Traversing rate	4 m/s
Acceleration	4 m/s <sup>2</sup>
Traversing direction	vertical, above the broadside
Max. bending cycles	10000000
Bending radius	50 mm
Special properties	Silicone-free
Halogen-free	yes
Ambient temperature (operation)	-40 °C ... 85 °C (cable, fixed installation)
	-30 °C ... 85 °C (cable, flexible installation)

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>