



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 24mm -0.5mm        |
| H  | 16.5mm -0.5mm      |
| T  | 11.3mm -0.5mm      |
| S  | 20.3mm +0.6/-0.1mm |
| H0 | 18.5mm +/-0.5mm    |
| F  | 0.8mm +/-0.05mm    |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, Large |
| Packaging Quantity | 400        |

### General Information

|               |  |
|---------------|--|
| Series        | PME261/P561                                |
| Dielectric    | Metallized Paper                           |
| Style         | Radial                                     |
| Features      | Pulse in DC and low frequency applications |
| RoHS          | Yes  |
| Lead          | Wire Leads                                 |
| AEC-Q200      | No   |
| Construction  | Molded                                     |
| Miscellaneous | AC Operation: 70C MAX.                     |

### Specifications

|                       |            |
|-----------------------|------------|
| Capacitance           | 0.33 uF    |
| Capacitance Tolerance | 5%         |
| Voltage AC            | 220 VAC    |
| Voltage DC            | 400 VDC    |
| Temperature Range     | -40/+100°C |
| Rated Temperature     | 85°C       |
| Dissipation Factor    | 1.3% 1kHz  |
| Insulation Resistance | 12 GOhms   |
| Max dV/dt             | 430 V/us   |