




## VMDTC75-55-M12-40-Z

Ruland VMDTC75-55-M12-40-Z, Vibration Isolation Mount, 75mm OD, M12 Tapped Holes, 12mm Tapped Hole Depths, 55mm Height, 40 Shore A Natural Rubber Jacket, Steel



### Description

Ruland VMDTC75-55-M12-40-Z is a vibration isolation mount with two tapped holes. It has a 75mm outside diameter, M12 tapped holes, 12mm tapped hole depths, and 55mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. VMDTC75-55-M12-40-Z can be mounted to the system by threading it onto an existing stud on the components. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 40 Shore A hardness for high dampening and shock absorption. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMDTC75-55-M12-40-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

### Product Specifications

<b>Outer Diameter (OD)</b>	2.95 in (75 mm)	<b>Height (H1)</b>	2.17 in (55 mm)
<b>Thread (TH)</b>	M12 x 1.75	<b>Plate Thickness (PT)</b>	0.12 in (3 mm)
<b>Tapped Hole Depth (LT)</b>	0.47 in (11.9 mm)	<b>Spring Rate</b>	1427.54 lb/in (250 N/mm)
<b>Shore Hardness</b>	40A (+/- 5)	<b>Max Deflection</b>	0.54 in (13.7 mm)
<b>Max Axial Load</b>	780.09 lb (3470 N)	<b>Geometry</b>	Cylindrical
<b>Rubber Material</b>	Natural Rubber	<b>Metal Material</b>	Zinc Plated Steel
<b>Metallic Body Finish</b>	Zinc-Plated	<b>Country of Origin</b>	Hungary
<b>Weight (lbs)</b>	0.910500	<b>UPC</b>	634529355008
<b>Tariff Code</b>	4016.99.6000	<b>UNSPC</b>	31162804
<b>Note 1</b>	Performance ratings are for guidance only. The user must determine suitability for a particular application.		