

LINEAR TECHNOLOGY MATERIALS DECLARATION

1t1120acn8#pbf

(Engineering Calculation)

PDIP

(printed on: 2020-07-11 19:08:10)

TOTAL MASS (g) : 0.501296

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.004009 | 1000000 | 7997.26611328 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.149760 | 975000 | 298745.4375 | | |
| | | Iron (Fe) | 7439-89-6 | 0.003686 | 24000 | 7352.93603516 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000046 | 300 | 91.7620925903 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000108 | 700 | 215.441421509 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.153600 | 1000000 | 306405.59375 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.012410 | 1000000 | 24756.3964844 | | |
| | | External Plating Total: | | | | 0.012410 | 1000000 | 24756.3964844 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.001228 | 1000000 | 2449.64892578 | | |
| Internal Plating Total: | | | | 0.001228 | 1000000 | 2449.64892578 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001110 | 750000 | 2214.2590332 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000370 | 250000 | 738.086364746 | | |
| Die Attach Total: | | | | 0.001480 | 1000000 | 2952.34545898 | | |
| Encapsulation | FILLED EPOXY RESIN | Resin (EP) | | 0.078816 | 240000 | 157224.359375 | | |
| | | Bromine (Br) | 40039-93-8 | 0.003284 | 10000 | 6551.015625 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.236448 | 720000 | 471673.09375 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.009852 | 30000 | 19653.0449219 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000000 | 0 | 0 | | |
| | | Encapsulation Total: | | | | 0.328400 | 1000000 | 655101.5 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000169 | 1000000 | 337.125976562 | | |
| | | | | | TOTAL MASS (g) : | 0.501296 | | |