

## Protect It! 3-Outlet Surge Protector, Direct Plug-In, 660 Joules, 2 Diagnostic LEDs

MODEL NUMBER: SK3-0



### Highlights

- 3 outlets/direct plug-in
- 660 joule rating
- Diagnostic LEDs

### Package Includes

- SK3-0 surge suppressor

### Description

The SK3-0 surge suppressor offers reliable surge and line noise protection. The compact direct plug-in design allows for easy portability and features 3 outlets and 660 joules of surge energy absorption. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- 3 outlets / direct plug-in
- Surge suppression rating: 660 joules
- EMI/RFI noise filtering
- Diagnostic LEDs indicate Protected (green) & Grounded (red)
- \$5,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

## Specifications

| OVERVIEW                           |                |
|------------------------------------|----------------|
| UPC Code                           | 037332166319   |
| INPUT                              |                |
| Nominal Input Voltage(s) Supported | 120V AC        |
| Recommended Electrical Service     | 120V           |
| Input Cord Length Details          | Direct Plug-In |
| Voltage Compatibility (VAC)        | 120            |

|  |  |
|--|--|
| Maximum Surge Amps                           | 39000  |
| Input Plug Type                              | NEMA 5-15P   |
| Input Cord Length (ft.)                      | 0  |
| Right-Angle Plug                             | No   |
| Input Cord Length (m)                        | 0.00   |
| Integrated Cord Clip                         | No   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 60 Hz  |
| Output Receptacles                           | (3) 5-15R  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | (2) Yes  |
| Right-Angle Outlets                          | No   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Diagnostic LED(s)                            | Yes  |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 660  |
| AC Suppression Response Time                 | < 1ns  |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| AC Suppression Surge Current Rating          | 27,000   |
| UL1449 Let Through Rating                    | 500, 400, 500  |
| EMI / RFI Filtering                          | Yes  |
| Immunity                                     | Conforms to IEE 587/ANSI C62.41  |
| Automatic Shut-Off                           | Yes  |
| <b>DATALINE SURGE SUPPRESSION</b>            |  |
| Cable (Coax) Protection                      | No   |
| Network (Ethernet) Protection                | No   |
| Telephone/DSL Protection                     | No   |
| <b>PHYSICAL</b>                              |  |
| Material of Construction                     | Plastic  |
| Mounting Holes or Slots                      | No   |
| Receptacle Color                             | Gray   |
| Shipping Dimensions (hwd / in.)              | 5.90 x 3.00 x 2.70   |

|  |   |
|--|---|
| Shipping Dimensions (hwd / cm)                             | 14.99 x 7.62 x 6.86   |
| Shipping Weight (lbs.)                                     | 0.32  |
| Shipping Weight (kg)                                       | 0.15  |
| Unit Dimensions (hwd / in.)                                | 2.500 x 3.800 x 2.100   |
| Unit Dimensions (hwd / cm)                                 | 6.35 x 9.7 x 5.33   |
| Unit Weight (lbs.)   | .20   |
| Unit Weight (kg)   | 0.09  |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |   |
| Antimicrobial  | No  |
| Rotatable Outlets  | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |   |
| Product Certifications                                     | UL 1449   |
| Product Compliance   | RoHS  |
| <b>WARRANTY &amp; SUPPORT</b>                              |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$5,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |