


.XX ±0.13 .XXX ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED



OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	40A (CURRENT)
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.

WITHSTANDING VOLTAGE:

1000V AC rms



					SW REFERENCE NO.: 629 COMBO ASSEMBLY					
	COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		19			
			CHECKED:		DATE:					
EDAC INC TORONTO, ONTARIO CANADA ARE THE PRO SHALL NOT BI OR USED AS	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.E	0. 1:1)	SHEET 1	OF	2			
	R USED AS THE BASIS FOR THE	DRAWING NUMBER: 629-13W6240-				ISSUE				
YOUR CONNECTION T	O QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER:	629-13W	6240-4T3		1			



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

