







**CYDLGF4LR**

**CYDLGF4LRL6-60V**

**CYDLGF4LRL110-240V**



**Dimensions & Weight**

	Fuse Block, 5x20mm with 4 Connection Points Bottom: Ground 2x2 Jumper Channels	Fuse Block, 5x20mm , LED with 4 Connection Points Bottom: Ground 2x2 Jumper Channels	Fuse Block, 5x20mm , LED with 4 Connection Points Bottom: Ground 2x2 Jumper Channels
<b>Width</b>	<b>6 mm</b>	<b>6 mm</b>	<b>6 mm</b>
<b>Length</b>	94.5 mm	94.5 mm	94.5 mm
<b>Height w DIN Rail</b>	35 x 7.5 mm 35 x 15 mm	90.9 mm 98.4 mm	90.9 mm 98.4 mm
<b>Weight per piece</b>	41.5 g	35.4 g	35.4 g

**Technical Data/Ratings**

Approvals			
<b>Wire Size (solid / stranded)</b>	<b>24-10 AWG</b>	0.2-4 mm <sup>2</sup>	<b>24-10 AWG</b>
<b>Voltage Rating</b>	300 V	1000V AC/DC	300 V
<b>Current Rating Fuse</b>	10 A	10 A	10 A
<b>Torque</b>	4.5 lb-in	0.5 Nm	4.5 lb-in
<b>Insulation Material</b>	Polyamide 66		

**Fuse Specifications**

<b>Fuse Type</b>	5x20 / 5x25 mm	5x20 / 5x25 mm	5x20 / 5x25 mm
<b>LED Indicator Voltage</b>	-	6-60V AC/DC	110-240V AC/DC

**Installation Instructions**

<b>Wire Stripping Length</b>	9 mm	9 mm	9 mm
<b>Screwdriver</b>	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

**Terminal Blocks**

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
<b>Grey (standard)</b>	<b>CYDLGF4LR</b>	50	<b>CYDLGF4LRL6-60L</b>	50	<b>CYDLGF4LRL110-240V</b>	50
Blue BU	CYDLGF4LR/BU	50	CYDLGF4LRL6-60L/BU	50	CYDLGF4LRL110-240V/BU	50
Black BL	CYDLGF4LR/BL	50	CYDLGF4LRL6-60L/BL	50	CYDLGF4LRL110-240V/BL	50

Additional colors available.



**Accessories**

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
<b>DIN Rail</b>	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
<b>End Stop</b>	CA702 CA802 CA202	50 50 50	CA702 CA802 CA202	50 50 50	CA702 CA802 CA202	50 50 50
<b>Shorting Link/Jumpers</b>	JX4/2 JX4/3 JX4/4	100 50 50	JX4/2 JX4/3 JX4/4	100 50 50	JX4/2 JX4/3 JX4/4	100 50 50
	5 pole 6 pole 7 pole 8 pole 10 pole 16 pole	- - - 10 10 10	- - - 10 10 10	- - - 10 10 10	- - - 10 10 10	- - - 10 10 10
<b>Marking Tag Warning Label</b>	MT6 WLX4	1 Pk. (100 tags) 1 Pk. (100 tags)	MT6 WLX4	1 Pk. (100 tags) 1 Pk. (100 tags)	MT6 WLX4	1 Pk. (100 tags) 1 Pk. (100 tags)

**FEATURES**

- Modified version of **CYDLGF4** with 2 equipotential Connections on each side
- 5x20mm fuse link
- Bottom Level Grounding Terminal
- 6mm wide compact design
- 2x2 internal jumper channels
- **CYDLGF4LRL** version with LED for blown fuse indication
- Blocks can be used in AC & DC applications

**APPLICATIONS**

- Tight Space Fuse applications
- Multi-wire fuse applications
- Control Systems with fuse applications