

ATGBICS FG-TRAN-SFP+ER-C network transceiver module Fiber optic 10000 Mbit/s 1550 nm

Brand : ATGBICS

Product code: FG-TRAN-SFP+ER-C

Product name : FG-TRAN-SFP+ER-C



Fortinet Compatible Transceiver SFP+ 10GBase-ER 1550nm SMF 40km LC DOM

ATGBICS FG-TRAN-SFP+ER-C network transceiver module Fiber optic 10000 Mbit/s 1550 nm:

ATGBICS FG-TRAN-SFP+ER 10GBase-ER supports a distance of up to 40km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Fortinet FG-TRAN-SFP+ER= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



| Performance | | Features | |
|--|---------------------|-----------------------------------|----------------|
| SFP transceiver type * | Fiber optic | Country of origin | United Kingdom |
| Maximum data transfer rate * | 10000 Mbit/s | Brand compatibility | Fortinet |
| Interface type * | SFP+ | Power | |
| Single-mode fiber (SMF) supported | ✓ | Input voltage | 3.3 V |
| Multi-mode fiber (MMF) supported | ✗ | Maximum voltage | 3.5 V |
| Fiber optic connector | LC | Power consumption (typical) | 1.5 W |
| SFP transceiver standard | ER | Operational conditions | |
| Maximum transfer distance | 40000 m | Maximum operating temperature | 70 °C |
| Wavelength | 1550 nm | Operating temperature (T-T) | 0 - 70 °C |
| Ethernet LAN | ✓ | Storage temperature (T-T) | -40 - 85 °C |
| Ethernet interface type | 10 Gigabit Ethernet | Operating relative humidity (H-H) | 0 - 95% |
| Digital Diagnostics Monitoring (DDM) | ✓ | Storage relative humidity (H-H) | 0 - 95% |
| Wavelength-division multiplexing (WDM) | ✗ | Weight & dimensions | |
| Features | | Width | 13.4 mm |
| Product colour | Silver | Depth | 56.5 mm |
| Housing material | Metal | Height | 8.5 mm |
| Plug and Play | ✓ | Weight | 19 g |
| Hot-Plug support | ✓ | Packaging data | |
| Hot-swap | ✓ | Number of products included | 1 pc(s) |
| Easy to install | ✓ | Package type | Box |
| | | Technical details | |
| | | Sustainability certificates | RoHS |



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.