

## Coaxial Cable Connector 24\_BNT-50-3-1/103\_N

### Description

Straight bulkhead cable feed through

Interface standards  
SUHNER-BNT



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 3 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0234 kg

#### Environmental Data

Operating temperature -50 °C to 125 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00048069  
Catalogue drawing DCA-00009150  
Assembly instruction DOC-0000179264  
Mounting hole DOU-00008751

### Ordering Information

Single package 24\_BNT-50-3-1/103\_NE

### Additional Information

Suitable cables G\_03332

### Remarks

Triaxial Connector