

# Contact insert module - HC-M-DSUB-09-UT-M - 1423723

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, number of positions: 9, type : D-SUB 9, Pin, Screw connection, 50 V, 1 A, 0.08 mm² ... 0.5 mm², application: Data



## Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626369419

## Technical data

### Dimensions

Height	35.7 mm
Width	34.2 mm
Length	14.6 mm

### Electrical characteristics

Rated voltage (III/3)	50 V
Rated current	1 A
Rated surge voltage	0.8 kV
Connection profile	9

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

### Mechanical characteristics

Conductor cross section	0.08 mm² ... 0.5 mm²
Connection cross section AWG	28 ... 20
Stripping length of the individual wire	4.2 mm
Tightening torque	0.03 Nm ... 0.05 Nm
Contact diameter	1 mm

# Contact insert module - HC-M-DSUB-09-UT-M - 1423723

## Technical data

### Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Minimum housing height	72 mm

### General

Note	For HEAVYCON housing type B6 to B48, HC-M-B...MF-... module carrier frame required
	Connectors may be operated only when there is no load/voltage.
Type	D-SUB 9
Series	HC-M-DSUB-U
Color	light gray
Number of module slots	1
Connection method	Screw connection
Contact type	turned
Flammability rating according to UL 94	V0
Degree of pollution	3
Overvoltage category	III
Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
	Use of HC-CST-MOD (1636127) coding pins and HC-CBU-MOD (1636130) coding sockets has been prescribed.

### Material data

Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC
Phase conductor material	Zinc alloy

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values