





Data sheet | Item number: 756-5311/090-050

Sensor/Actuator cable; M12A plug; straight; 8-pole; Length: 5 m

www.wago.com/756-5311/090-050



i Picture differs from the item.



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	1.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	5 m
Type code	LiF9YH-11YH or LiF9YC11YFHF

Subject to changes. Please also observe the further product documentation!



Conductor configuration	Bare copper wire, fine-stranded (32 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	6.1 ... 6.5 mm

Connector

Connection type	M12 plug - free end
Cable connection direction to mating direction	0°
Connector interface coding (cable/adapter) 1 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	HU
GTIN	4050821346371
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	152558c6-b5fc-4ebc-9aed-a2fb6b08a217
SCIP notification number (Belgium)	3a9cf0d7-9259-436f-9dc1-2aca54cf45de
SCIP notification number (Bulgaria)	60487d13-c285-42b9-ab08-c345f9f61d3f
SCIP notification number (Czech Republic)	312cb167-c735-4845-9068-dde807c7525d
SCIP notification number (Denmark)	9f4ac926-3af1-4064-add0-ed816df6b54a
SCIP notification number (Finland)	f13c7679-46ce-4e3e-95b5-b39485331f9e

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com


Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



SCIP notification number (France)	f0372911-2b26-401a-86ab-c2f6efc7c880
SCIP notification number (Germany)	54fb2bde-f610-45d7-a104-5a1c4281c5fe
SCIP notification number (Hungary)	7663886e-bdba-4b47-8499-75f444109176
SCIP notification number (Italy)	5650e971-4e7a-4bd7-903b-9ccc8c49e1c9
SCIP notification number (Netherlands)	625cc1d7-a665-4978-86e6-2f444d755129
SCIP notification number (Poland)	d0973d12-5bcb-4f73-863e-10f7a34fab6e
SCIP notification number (Romania)	59dd6a2a-b740-45be-b405-c4a465f8bd4b
SCIP notification number (Sweden)	b31e5b7c-0918-419f-bca3-95c38be7ed54

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5311/090-050 X81 - Datei	2019 Feb 19	xml 3.4 kB	Download
756-5311/090-050 doc - Datei	2017 Sep 20	doc 27.6 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5311/090-050 Sensor/Actuator cable; M12A plug; straight; 8-pole; Length: 5 m	URL	Download
--	-----	----------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.