

CATHODE (-) END VIEW



SIDE VIEW



ANODE (+) END VIEW



BOTTOM VIEW



Click [here](#) for the 3D model.

### Dimensions

|           |                 |
|-----------|-----------------|
| Footprint | 7343            |
| L         | 7.3mm +/-0.3mm  |
| W         | 4.3mm +/-0.3mm  |
| H         | 4mm +/-0.3mm    |
| T         | 0.13mm REF      |
| S         | 1.3mm +/-0.3mm  |
| F         | 2.4mm +/-0.1mm  |
| A         | 3.6mm MIN       |
| B         | 0.5mm +/-0.15mm |
| E         | 3.5mm REF       |
| G         | 3.5mm REF       |
| P         | 1.7mm REF       |
| R         | 1mm REF         |
| X         | 0.1mm +/-0.1mm  |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 178mm |
| Packaging Quantity | 500        |

### General Information

|                  |   |
|------------------|---|
| Series           | T494                                    |
| Dielectric       | MnO <sub>2</sub> Tantalum               |
| Style            | SMD Chip                                |
| Description      | SMD, MnO <sub>2</sub> , Molded, Low ESR |
| Features         | Low ESR                                 |
| RoHS             | Yes                                     |
| Termination      | Tin                                     |
| AEC-Q200         | No                                      |
| Component Weight | 652.04 mg                               |
| Shelf Life       | 156 Weeks                               |
| MSL              | 1                                       |

### Specifications

|                       |  |
|-----------------------|--|
| Capacitance           | 150 uF   |
| Capacitance Tolerance | 10%  |
| Voltage DC            | 16 VDC (85C), 10.72 VDC (125C)                                       |
| Temperature Range     | -55/+125°C   |
| Rated Temperature     | 85°C   |
| Dissipation Factor    | 8% 120Hz 25C   |
| Failure Rate          | N/A  |
| Resistance            | 0.15 Ohms (100kHz 25C)   |
| Ripple Current        | 1049 mA (rms, 100kHz 25C), 944.1 mA (rms, 85C), 419.6 mA (rms, 125C) |
| Leakage Current       | 24 uA (5min 25°C)  |