



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 55.92 g ± 10%

| Connector dimension |                |
|---------------------|----------------|
| Dim                 | Nominal        |
| A                   | 52.4±0.3       |
| B                   | 36.5+0.1/-0.15 |
| R                   | 32.5Max        |
| S                   | 49.2±0.4       |
| W                   | 3+0.9/-0.1     |
| VV THREAD           | M31x1-6g       |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |


PN: 8D721Z39SAL

|                |                                |                                |   |
|----------------|--------------------------------|--------------------------------|---|
| A              | 08-11-2016                     | First Release                  |   |
| ISS            | DATE                           | Latest modification - by       | MOD N°  |
| Designed By:   |                                | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series |                                |   |
| SCALE          | NA                             | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>         |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>A3</b>                      |                                | <b>SOURIAU DRG N° 8D721Z39SAL-C</b>   |
|                |                                |                                | SHEET 1/2   |

BASIC SERIES: 8D 7 - 21 Z 39 S A L  
 SHELL TYPE : Jam nut Receptacle  
 CONTACT TYPE : Standard Crimp Contact  
 SHELL SIZE : 21  
 PLATING : Z = Black Zinc Nickel

Delivered W/O Contacts  
 ORIENTATION : A  
 CONTACT TYPE : SOCKET(500 Matings)  
 CONTACT LAYOUT : 21-39

Contact Layout



| Contacts<br>(Insert arrangement 21-39) |              |              |                     |             |             |
|--|--------------|--------------|---------------------|-------------|-------------|
| Contact position ID                    | Location     |              | Contact position ID | Location    |             |
|  | X-axis (mm)  | Y-axis (mm)  |                     | X-axis (mm) | Y-axis (mm) |
| A                                      | +065 (1.65)  | +411 (10.44) | X                   | +000 (0.00) | +295 (7.49) |
| B                                      | +189 (4.80)  | +371 (9.42)  | Y                   | +126 (3.20) | +256 (6.50) |
| C                                      | +294 (7.47)  | +294 (7.47)  | Z                   | +232 (5.89) | +179 (4.55) |
| D                                      | +371 (9.42)  | +189 (4.80)  | a                   | +280 (7.11) | +057 (1.45) |
| E                                      | -411 (10.44) | +065 (1.65)  | b                   | -280 (7.11) | -074 (1.88) |
| F                                      | +411 (10.44) | -065 (1.65)  | c                   | +217 (5.51) | -189 (4.80) |
| G                                      | +371 (9.42)  | -189 (4.80)  | d                   | +112 (2.84) | -265 (6.73) |
| H                                      | +294 (7.47)  | -294 (7.47)  | e                   | -112 (2.84) | -265 (6.73) |
| J                                      | +189 (4.80)  | -371 (9.42)  | f                   | -217 (5.51) | -189 (4.80) |
| K                                      | +065 (1.65)  | -411 (10.44) | g                   | -280 (7.11) | -074 (1.88) |
| L                                      | -065 (1.65)  | -411 (10.44) | h                   | -280 (7.11) | +057 (1.45) |
| M                                      | -189 (4.80)  | -371 (9.42)  | i                   | -232 (5.89) | +179 (4.55) |
| N                                      | -294 (7.47)  | -294 (7.47)  | j                   | -126 (3.20) | +256 (6.50) |
| P                                      | -371 (9.42)  | -189 (4.80)  | k                   | +000 (0.00) | +164 (4.17) |
| R                                      | -411 (10.44) | -065 (1.65)  | m                   | +114 (2.90) | +048 (1.22) |

| Contacts<br>(Insert arrangement 21-39) |              |              |                     |             |             |
|--|--------------|--------------|---------------------|-------------|-------------|
| Contact position ID                    | Location     |              | Contact position ID | Location    |             |
|  | X-axis (mm)  | Y-axis (mm)  |                     | X-axis (mm) | Y-axis (mm) |
| S                                      | -411 (10.44) | +065 (1.65)  | n                   | +106 (2.69) | -107 (2.72) |
| T                                      | -371 (9.42)  | +189 (4.80)  | p                   | +000 (0.00) | -189 (4.80) |
| U                                      | -294 (7.47)  | +294 (7.47)  | q                   | -106 (2.69) | -107 (2.72) |
| V                                      | -189 (4.80)  | +371 (9.42)  | r                   | -114 (2.90) | +048 (1.09) |
| W                                      | -065 (1.65)  | +411 (10.44) | ---                 | ---         | ---         |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location   | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|--------------------|------------|
| 21         | -39             | 2<br>37            | 16<br>20      | I              | f, m<br>All others | MS20055-39 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



Max. thickness panel for receptacle: Type 7: 3.2 mm

| Dim | Nominal       |
|-----|---------------|
| B   | 37.08+0/-0.25 |
| ØC  | 38.35+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D721Z39SAL

|                |                                     |                            |   |
|----------------|-------------------------------------|----------------------------|---|
| A              | 08-11-2016                          | First Release              |   |
| ISS            | DATE                                | Latest modification - by   | MOD N°  |
| Designed By:   |                                     | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series      |                            |   |
| SCALE          |                                     | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                     | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>              |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D721Z39SAL-C</b> |                            | SHEET 2/2   |