



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

| Connector dimension |           |
|---------------------|-----------|
| Dim                 | Nominal   |
| F                   | 19.05 Max |
| Z                   | 31.5 Max  |
| VV THREAD           | M15x1-6g  |

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 48 hours

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D111F35SB**

|              |                                 |                                    |   |
|--------------|---------------------------------|------------------------------------|---|
| A            | 26-09-2016                      | First Release                      |   |
| ISS          | DATE                            | Latest modification - by           | MOD N°  |
| Designed By: |                                 | Date:                              | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b> | Aluminium Inline plug 8D series |                                    |   |
| SCALE        |                                 | General linear Tolerances: ±--     | NPRDS / PROJECT<br><b>859</b>   |
| NA           | <br><b>WWW.SOURIAU.COM</b>      |                                    | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT       | <b>A3</b>                       |                                    | SHEET<br>1/2  |
|              |                                 | <b>SOURIAU DRG N° 8D111F35SB-C</b> |   |

|                |                        |   |   |    |   |    |   |   |                                    |
|----------------|------------------------|---|---|----|---|----|---|---|------------------------------------|
| BASIC SERIES:  | 8D                     | 1 | - | 11 | F | 35 | S | B | ORIENTATION : B                    |
| SHELL TYPE :   | In line Receptacle     |   |   |    |   |    |   |   | CONTACT TYPE : SOCKET(500 Matings) |
| CONTACT TYPE : | Standard Crimp Contact |   |   |    |   |    |   |   | CONTACT LAYOUT : 11-35             |
| SHELL SIZE :   | 11                     |   |   |    |   |    |   |   |                                    |
| PLATING :      | F = Nickel             |   |   |    |   |    |   |   |                                    |

4  
3  
2  
1

**Contact Layout**



| Contacts<br>(Insert arrangement 11-35) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| 1                                      | +000 (0.00) | +146 (3.71) | 8                   | -138 (3.51) | -045 (1.14) |
| 2                                      | +085 (2.16) | +118 (3.00) | 9                   | -138 (3.51) | +045 (1.14) |
| 3                                      | +138 (3.51) | +045 (1.14) | 10                  | -085 (2.16) | +118 (3.00) |
| 4                                      | +138 (3.51) | -045 (1.14) | 11                  | +000 (0.00) | +056 (1.42) |
| 5                                      | +085 (2.16) | -118 (3.00) | 12                  | +049 (1.24) | -035 (0.89) |
| 6                                      | +000 (0.00) | -146 (3.71) | 13                  | -049 (1.24) | -035 (0.89) |
| 7                                      | -085 (2.16) | -118 (3.00) | ---                 | ---         | ---         |

(Applicable to MIL-DTL-38999 only)

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 11         | -35             | 13                 | 22D           | M              | All              | MS27526-35 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D111F35SB**

|                |  |                            |   |
|----------------|--|----------------------------|---|
| A              | 26-09-2016                             | First Release              |   |
| ISS            | DATE                                   | Latest modification - by   | MOD N°  |
| Designed By:   |  | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Aluminium Inline plug 8D series</b> |                            |   |
| SCALE          |  | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |  | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                 |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D111F35SB-C</b>     |                            | SHEET 2/2   |