


ESD-R-19

Aliases (UECESDR1900000)

KEMET, ESD-R, EMI Cores, Noise Suppression



Click here for the 3D model.

Dimensions		
D	19mm +/-1.0mm	
D2	9mm +/-1.0mm	
Т	11mm +/-1.0mm	

Packaging Specifications	
Packaging	Tray, Box
Packaging Quantity	480
Component Weight	11.1 g

General Information		
Series	ESD-R	
Style	Round - Toroidal	
,	Round Cable	
Cable Type	Trouting Gubic	
Description	EMI Core Solid, For Round Cables, Toroidal Cores With Case	
RoHS	Yes	
Qualifications	UL94 V-2	
Case Color	White	
Toroidal	ESD-R-19S	
Materials	Mn-Zn	

Specifications	
Temperature Range	-25/+85°C
Effective Frequency	10 MHz (AM Band Range)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.