



Figure similar

MLFB-Ordering data

6SL3230-1YE18-0UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data | | General tech. specifications | |
|-------------------------------------|---------------------------|--|--|
| Input | | | |
| Number of phases | 3 AC | | |
| Line voltage | 380 ... 480 V +10 % -20 % | | |
| Line frequency | 47 ... 63 Hz | | |
| Rated voltage | 400V IEC | 480V NEC | |
| Rated current (LO) | 6.90 A | 5.80 A | |
| Rated current (HO) | 5.29 A | 4.60 A | |
| Output | | | |
| Number of phases | 3 AC | | |
| Rated voltage | 400V IEC | 480V NEC | |
| Rated power (LO) | 3.00 kW | 4.00 hp | |
| Rated power (HO) | 2.20 kW | 3.00 hp | |
| Rated current (LO) | 7.70 A | 6.20 A | |
| Rated current (HO) | 5.90 A | 4.80 A | |
| Rated current (IN) | 8.00 A | | |
| Max. output current | 9.10 A | | |
| Pulse frequency | 4 kHz | | |
| Output frequency for vector control | 0 ... 200 Hz | | |
| Output frequency for V/f control | 0 ... 550 Hz | | |
| Power factor λ | | 0.70 ... 0.85 | |
| Offset factor $\cos \phi$ | | 0.96 | |
| Efficiency η | | 0.98 | |
| Sound pressure level (1m) | | 55 dB | |
| Power loss | | 0.126 kW | |
| Filter class (integrated) | | Unfiltered | |
| EMC category (with accessories) | | without | |
| Ambient conditions | | | |
| Standard board coating type | | Class 3C3, according to IEC 60721-3-3: 2002 | |
| Cooling | | Air cooling using an integrated fan | |
| Cooling air requirement | | 0.005 m ³ /s (0.177 ft ³ /s) | |
| Installation altitude | | 1000 m (3280.84 ft) | |
| Ambient temperature | | | |
| Operation | | -20 ... 45 °C (-4 ... 113 °F) | |
| Transport | | -40 ... 70 °C (-40 ... 158 °F) | |
| Storage | | -25 ... 55 °C (-13 ... 131 °F) | |
| Relative humidity | | | |
| Max. operation | | 95 % At 40 °C (104 °F), condensation and icing not permissible | |

Overload capability

Low Overload (LO)

110% base load current IL for 60 s in a 300 s cycle time

High Overload (HO)

150% x base load current IH for 60 s within a 600 s cycle time



Figure similar

MLFB-Ordering data

6SL3230-1YE18-0UF0

Mechanical data

| | |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Size | FSA |
| Net weight | 3 kg (7.05 lb) |
| Width | 73 mm (2.87 in) |
| Height | 232 mm (9.13 in) |
| Depth | 218 mm (8.58 in) |

Inputs / outputs

Standard digital inputs

| | |
|----------------------|-------|
| Number | 6 |
| Switching level: 0→1 | 11 V |
| Switching level: 1→0 | 5 V |
| Max. inrush current | 15 mA |

Fail-safe digital inputs

| | |
|--------|---|
| Number | 1 |
|--------|---|

Digital outputs

| | |
|------------------------------------|----------------|
| Number as relay changeover contact | 2 |
| Output (resistive load) | DC 30 V, 5.0 A |
| Number as transistor | 0 |

Analog / digital inputs

| | |
|------------|------------------------|
| Number | 2 (Differential input) |
| Resolution | 10 bit |

Switching threshold as digital input

| | |
|-----|-------|
| 0→1 | 4 V |
| 1→0 | 1.6 V |

Analog outputs

| | |
|--------|-------------------------|
| Number | 1 (Non-isolated output) |
|--------|-------------------------|

PTC/ KTY interface

1 motor temperature sensor input, sensors that can be connected: PTC, KTY and Thermo-Click, accuracy ±5 °C

Closed-loop control techniques

| | |
|---|-----|
| V/f linear / square-law / parameterizable | Yes |
| V/f with flux current control (FCC) | Yes |
| V/f ECO linear / square-law | Yes |
| Sensorless vector control | Yes |
| Vector control, with sensor | No |
| Encoderless torque control | Yes |
| Torque control, with encoder | No |

Communication

| | |
|---------------|-----------------------|
| Communication | PROFINET, EtherNet/IP |
|---------------|-----------------------|

Connections

Signal cable

| | |
|-------------------------|--|
| Conductor cross-section | 0.15 ... 1.50 mm ² (AWG 24 ... AWG 16) |
|-------------------------|--|

Line side

| | |
|-------------------------|--|
| Version | screw-type terminal |
| Conductor cross-section | 1.50 ... 2.50 mm ² (AWG 16 ... AWG 14) |

Motor end

| | |
|-------------------------|--|
| Version | Screw-type terminals |
| Conductor cross-section | 1.50 ... 2.50 mm ² (AWG 16 ... AWG 14) |

DC link (for braking resistor)

| | |
|---------------|--------------------------|
| PE connection | On housing with M4 screw |
|---------------|--------------------------|

Max. motor cable length

| | |
|------------|-------------------|
| Shielded | 150 m (492.13 ft) |
| Unshielded | 300 m (984.25 ft) |




Figure similar

MLFB-Ordering data

6SL3230-1YE18-0UF0

Converter losses to EN 50598-2*

| | |
|--|----------|
| Efficiency class | IE2 |
| Comparison with the reference converter (90% / 100%) | -37.40 % |



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*converted values

Standards

Compliance with standards UL, cUL, CE, C-Tick (RCM), EAC, KCC, SEMI F47, REACH

CE marking

EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC