

1

2

3

4

5

6

7




A

MA 001C (DB9M/25M ADAPTOR)

PIN OUT:

09Male 25Male

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G



Label: orange color with white character
 One side: SERIAL PORT ADAPTORS D9/D25
 The other side: MINI ADAPTER
 SPECIFICATION
 INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell

G

Scale	Free	Date	Name	Customer-No.
TOLERANCE		08.04.2017	Winnie	ASSMANN WSW-No.
X.X	0.20			AB467
X.XX	±0.15			
X.XXX	±0.05			
DIM	TOL			

H

Scale	Free	Date	Name	Customer-No.
TOLERANCE		08.04.2017	Winnie	ASSMANN WSW-No.
X.X	0.20			AB467
X.XX	±0.15			
X.XXX	±0.05			
DIM	TOL			

RoHS compliant
Unit: mm

Scale	Free	Date	Name	Customer-No.
TOLERANCE		08.04.2017	Winnie	ASSMANN WSW-No.
X.X	0.20			AB467
X.XX	±0.15			
X.XXX	±0.05			
DIM	TOL			

H

Scale	Free	Date	Name	Customer-No.
TOLERANCE		08.04.2017	Winnie	ASSMANN WSW-No.
X.X	0.20			AB467
X.XX	±0.15			
X.XXX	±0.05			
DIM	TOL			

1

2

3

4

5

6

7

H



ASS 7553 CO

rev00

Replace

Sheet