

Contact Layout



Contacts (Insert arrangement 17-35)					
Contact position ID	Location		Contact position ID	Location	
	X-axis (mm)	Y-axis (mm)		X-axis (mm)	Y-axis (mm)
1	-312 (7.92)	+086 (2.18)	29	.000 (0.00)	-.094 (2.39)
2	-312 (7.92)	-.004 (0.10)	30	.000 (0.00)	-.184 (4.67)
3	-312 (7.92)	-.094 (2.39)	31	.000 (0.00)	-.274 (6.96)
4	-.242 (6.15)	+221 (5.61)	32	+.089 (2.26)	+.316 (8.03)
5	-.234 (5.94)	+131 (3.33)	33	+.078 (1.98)	+.221 (5.61)
6	-.234 (5.94)	+.041 (1.04)	34	+.078 (1.98)	+.131 (3.33)
7	-.234 (5.94)	-.049 (1.24)	35	+.078 (1.98)	+.041 (1.04)
8	-.234 (5.94)	-.139 (3.53)	36	+.078 (1.98)	-.049 (1.24)
9	-.234 (5.94)	-.229 (5.82)	37	+.078 (1.98)	-.139 (3.53)
10	-.172 (4.37)	+.279 (7.09)	38	+.078 (1.98)	-.229 (5.82)
11	-.156 (3.96)	+176 (4.47)	39	+.078 (1.98)	-.319 (8.10)
12	-.156 (3.96)	+086 (2.18)	40	+.172 (4.37)	+.279 (7.09)
13	-.156 (3.96)	-.004 (0.10)	41	+.156 (3.96)	+.176 (4.47)
14	-.156 (3.96)	-.094 (2.39)	42	+.156 (3.96)	+086 (2.18)
15	-.156 (3.96)	-.184 (4.67)	43	+.156 (3.96)	-.004 (0.10)
16	-.156 (3.96)	-.274 (6.96)	44	+.156 (3.96)	-.094 (2.39)
17	-.089 (2.26)	+.316 (8.03)	45	+.156 (3.96)	-.184 (4.67)
18	-.078 (1.98)	+221 (5.61)	46	+.156 (3.96)	-.274 (6.96)

Contacts (Insert arrangement 17-35)					
Contact position ID	Location		Contact position ID	Location	
	X-axis (mm)	Y-axis (mm)		X-axis (mm)	Y-axis (mm)
19	-.078 (1.98)	+131 (3.33)	47	+.242 (6.15)	+.221 (5.61)
20	-.078 (1.98)	+.041 (1.04)	48	+.234 (5.94)	+.131 (3.33)
21	-.078 (1.98)	-.049 (1.24)	49	+.234 (5.94)	+.041 (1.04)
22	-.078 (1.98)	-.139 (3.53)	50	+.234 (5.94)	-.049 (1.24)
23	-.078 (1.98)	-.229 (5.82)	51	+.234 (5.94)	-.139 (3.53)
24	-.078 (1.98)	-.319 (8.10)	52	+.234 (5.94)	-.229 (5.82)
25	.000 (0.00)	+.329 (8.36)	53	+.312 (7.92)	+.086 (2.18)
26	.000 (0.00)	+176 (4.47)	54	+.312 (7.92)	-.004 (0.10)
27	.000 (0.00)	+086 (2.18)	55	+.312 (7.92)	-.094 (2.39)
28	.000 (0.00)	-.004 (0.10)	---	---	---

Shell size	Arrangement no.	Number of contacts	Size contacts	Service rating	Contact location	Supersedes
17	-35	55	22D	M	All	MS27529-35

Panel Cutout



Max. thickness panel for receptacle: Type 0: front mounting = 3.2 mm, rear mounting = 2.5 mm

Dim	Nominal
ØA	30.96 min
ØAA	25.81 min
R1	26.97
ØT	3.25 ±0.13

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D017S35AE

B	11-04-17	Drawing Update	
ISS	DATE	Latest modification - by	MOD N°
Designed By:		Date:	CUSTOMER DRAWING
TITLE	Stainless Steel Receptacle 8D series		
SCALE		General linear Tolerances: ±--	NPRDS / PROJECT 859
NA		This document is the property of SOURIAU it must not be reproduced or communicated without permission	
SOURIAU	WWW.SOURIAU.COM		
FORMAT	SOURIAU DRG N° 8D017S35AE-C		SHEET 2/2