



3 Type

- A** Mounting from the back (tapped blind hole)
- B** Mounting from the operator's side (only for $b_1 = 20\text{ mm}$)

Metric table

Dimensions in: millimeters - inches

1 b_1	2 $l_1 \pm 0.25$	a	b₂	d Thread	h₁	h₂	h₃	l₂	l₃	l₄	r	t₁ min.	t₂
20 0.79	130 5.12	10 0.39	23 0.91	M 5	45 1.77	6.5 0.26	2.5 0.10	120 4.72	141 5.55	153 6.02	15 0.59	10 0.39	5 0.20
20 0.79	170 6.69	10 0.39	23 0.91	M 5	45 1.77	6.5 0.26	2.5 0.10	160 6.30	181 7.13	193 7.60	15 0.59	10 0.39	5 0.20
20 0.79	190 7.48	10 0.39	23 0.91	M 5	45 1.77	6.5 0.26	2.5 0.10	180 7.09	201 7.91	213 8.39	15 0.59	10 0.39	5 0.20
20 0.79	210 8.27	10 0.39	23 0.91	M 5	45 1.77	6.5 0.26	2.5 0.10	200 7.87	221 8.70	233 9.17	15 0.59	10 0.39	5 0.20
30 1.18	262 10.31	12 0.47	-	M 6	50 1.97	-	-	250 9.84	-	-	15 0.59	12 0.47	-
30 1.18	312 12.28	12 0.47	-	M 6	50 1.97	-	-	300 11.81	-	-	15 0.59	12 0.47	-
30 1.18	362 14.25	12 0.47	-	M 6	50 1.97	-	-	350 13.78	-	-	15 0.59	12 0.47	-
30 1.18	412 16.22	12 0.47	-	M 6	50 1.97	-	-	400 15.75	-	-	15 0.59	12 0.47	-

Specification

- Aluminum
 - Powder coated
 - Black, RAL 9005, textured finish **● SW**
 - Silver, RAL 9006, textured finish **● SR**
 - Plain, tumbled finish **○ BL**
- Handle base
 - Plastic
 - Technopolymer (Polyamide PA)
 - Black, matte finish (for SW / BL)
 - Light gray, matte finish (for SR)
- Load Rating Information → page 2068
- Plastic Characteristics → page 2135
- RoHS compliant

Information

GN 668 cabinet "U" handles are manufactured from a bent aluminum profile with a smooth surface and rigid design. The shape of the handle has good ergonomic features.

The manufacturing process allows the production of special lengths in relatively small quantities.

see also...

- "Economical" Cabinet "U" Handles GN 728
(Aluminum, Mounting from the Back or from the Operator's Side) → page 120

On request

- Special lengths
- Various metric size fasteners and kit packaging

How to order GN 668-20-170-B-SW	1 Handle width b_1
	2 Length l_1
	3 Type
	4 Finish