



Click [here](#) for the 3D model.

### Dimensions

|    |                    |
|----|--------------------|
| L  | 26.5mm +0.3/-0.5mm |
| H  | 15mm +0.1/-0.5mm   |
| T  | 6mm +0.2/-0.5mm    |
| S  | 22.5mm +/-0.4mm    |
| H0 | 18.5mm +/-0.5mm    |
| F  | 0.8mm +/-0.05mm    |

### Packaging Specifications

|                    |                         |
|--------------------|-------------------------|
| Packaging          | Ammo, 360x340x59mm, Box |
| Packaging Quantity | 464                     |

### General Information

|                |                                 |
|----------------|---------------------------------|
| Series         | R76                             |
| Dielectric     | Double Metallized Polypropylene |
| Style          | Radial                          |
| Features       | Automotive Grade, Pulse         |
| RoHS           | Yes                             |
| Lead           | Wire Leads                      |
| Qualifications | AEC-Q200                        |
| AEC-Q200       | Yes                             |

### Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Capacitance           | 2200 pF                              |
| Capacitance Tolerance | 10%                                  |
| Voltage AC            | 700 VAC                              |
| Voltage DC            | 2000 VDC                             |
| Temperature Range     | -55/+110°C                           |
| Rated Temperature     | 85°C                                 |
| Dissipation Factor    | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz |
| Insulation Resistance | 100 GOhms                            |
| Max dV/dt             | 4500 V/us                            |
| Resistance            | 289.37 mOhms (100kHz)                |
| Ripple Current        | 1 Amps (100kHz 85C), 10 Amps (Peak)  |
| Inductance            | 16 nH                                |