

## TMB-CP 2,5/10 - 3207716

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 25 pc    |
| Weight per Piece (excluding packing) | 17.864 g |
| Country of origin                    | Poland   |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141131 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211802 |
| UNSPSC 7.0901 | 39121402 |
| UNSPSC 11     | 39121402 |
| UNSPSC 12.01  | 39121402 |
| UNSPSC 13.2   | 39121402 |

### Approvals

#### Approvals

# TMB-CP 2,5/10 - 3207716

## Approvals

Approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

## Approval details

|                                |       |
|--------------------------------|-------|
| CSA                            |       |
|                                | C     |
| mm <sup>2</sup> /AWG/kcmil     | 14    |
| Nominal current I <sub>N</sub> | 20 A  |
| Nominal voltage U <sub>N</sub> | 600 V |

|                                |       |
|--------------------------------|-------|
| UL Recognized                  |       |
|                                |       |
| mm <sup>2</sup> /AWG/kcmil     | 14    |
| Nominal current I <sub>N</sub> | 20 A  |
| Nominal voltage U <sub>N</sub> | 600 V |

|                                |       |
|--------------------------------|-------|
| cUL Recognized                 |       |
|                                |       |
| mm <sup>2</sup> /AWG/kcmil     | 14    |
| Nominal current I <sub>N</sub> | 15 A  |
| Nominal voltage U <sub>N</sub> | 600 V |

|                  |  |
|------------------|--|
| cULus Recognized |  |
|------------------|--|

