

Data sheet | Item number: 756-5403/040-010




Sensor/Actuator cable; M12A socket; angled; M12A plug; straight; 4-pole;  
Length: 1 m



[www.wago.com/756-5403/040-010](http://www.wago.com/756-5403/040-010)



 Picture differs from the item.



### Item description

#### Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## Data

### Technical data

#### General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

#### Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

#### Cable

Cable length	1 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.5 ... 4.9 mm

#### Connector

Connection type	M12 Socket - M12 plug
Cable connection direction to mating direction	90 °
Cable connection direction to mating direction (2)	0 °

Subject to changes. Please also observe the further product documentation!



Connector interface coding (cable/adapter) 1 1	A-coded
Connector interface coding (cable/adapter) 2 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

## Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	HU
GTIN	4044918975551
Customs tariff number	85444290900

## Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	4c3e4569-fd62-499c-bd56-09a79d4967f1
SCIP notification number (Belgium)	98951683-d5d5-4aad-8c92-cc829f278a5c
SCIP notification number (Bulgaria)	ed9fe69e-54ca-44ac-afdc-6bd555918aac
SCIP notification number (Czech Republic)	b568b021-3cc9-444e-a320-7c8d14ab3d45
SCIP notification number (Denmark)	84de3c94-cb6c-47d9-b788-25745b7c7d06
SCIP notification number (Finland)	b1cab41-1a3a-46f1-9451-8d502c6087ca
SCIP notification number (France)	f8b228a6-eb8f-4076-83f2-062664d7c781
SCIP notification number (Germany)	4bdbf50c-ee89-4cc0-b74f-48c0cc4f4fad
SCIP notification number (Hungary)	6a57618b-0d53-4cf1-b3eb-75ca6073d2f8
SCIP notification number (Italy)	5e1a7501-2f10-47fe-9963-b2196cc18633
SCIP notification number (Netherlands)	95567c8a-f09d-4f4a-b2a4-ef6be689d62b
SCIP notification number (Poland)	a8c31d7a-7605-48b0-a777-1b5c09fdf702
SCIP notification number (Romania)	8008fe6a-551b-4b9e-872b-0aa1be65bf89
SCIP notification number (Sweden)	fc238269-1327-49aa-a697-ba5c3613efa7


Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.

## Approvals / Certificates

### General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

## Downloads

### Documentation

#### Bid Text

756-5403/040-010 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5403/040-010 doc - Datei	2017 Sep 20	doc 27.1 kB	Download

#### System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

## CAD/CAE-Data

### CAE data

WSCAD Universe 756-5403/040-010	URL	Download
WSCAD Universe 756-5403/040-010	URL	Download

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 756-5403/040-010 Sensor/Actuator cable; M12A socket; angled; M12A plug; straight; 4-pole; Length: 1 m	URL	Download
---	-----	----------

Subject to changes. Please also observe the further product documentation!



## Installation Notes

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.