

# GPS Active Antenna Module - Adhesive Mount

## APAMP-113

RoHS/RoHS II compliant

Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-1)



38.0 X 34.0 X 12mm

MSL level: Not Applicable

### FEATURES:

- High Reliability/Sensitivity
- Compact Size
- Easy to install (adhesive base tape)
- ROHS Compliant

### TYPICAL APPLICATIONS:

- Automotive Navigation
- Automotive Monitoring
- Personal Tracking

### STANDARD SPECIFICATIONS:

#### Antenna

| Parameters               | Min.    | Typ.    | Max.    | Units              | Note                               |
|--------------------------|---------|---------|---------|--------------------|------------------------------------|
| Center Frequency         | 1574.40 | 1575.42 | 1576.44 | MHz                |                                    |
| Bandwidth                | 10.0    |         |         | MHz                |                                    |
| VSWR at Center Frequency |         |         | 1.5:1   |                    |                                    |
| Polarization Model       | RHCP    |         |         |                    | (Right Hand Circular Polarization) |
| Impedance                |         | 50      |         | $\Omega$           |                                    |
| Gain                     |         | 5       |         | dBic               | (Based on 70x 70mm ground plane)   |
| Operating Temperature    | -40     |         | +80     | $^{\circ}\text{C}$ |                                    |
| Storage Temperature      | -45     |         | +85     | $^{\circ}\text{C}$ |                                    |

#### Low Noise Amplifier (LNA)

| Parameters                             | Min.    | Typ.    | Max.    | Units | Note  |
|--|---------|---------|---------|-------|---|
| Center Frequency                       | 1574.40 | 1575.42 | 1576.44 | MHz   |   |
| DC Voltage                             | 3.0     |         | 5.0     | V     |   |
| Gain                                   | 25      | 28      | 31      | dB    | (+25 $^{\circ}\text{C}$ $\pm$ 10 $^{\circ}\text{C}$ ) |
| Out-of-band Rejection (Absolute Value) | 19      |         |         | dB    | (Fo+100MHZ)   |
|  | 21      |         |         | dB    | (Fo-100MHZ)   |
| Output VSWR                            |         |         | 2.0     |       |   |
| Noise Figure                           |         |         | 1.8     |       |   |
| DC current                             |         | 7.5     | 9.5     | mA    | (At 3.0V)   |

#### Overall (Complete module including RF connector)

| Parameters       | Min.    | Typ.    | Max.     | Units    | Note               |
|------------------|---------|---------|----------|----------|--------------------|
| Center Frequency | 1574.40 | 1575.42 | 1576.44  | MHz      |                    |
| Gain             | 25      | 28      | 31       | dBic     |                    |
| Output VSWR      |         |         | 2.0      |          |                    |
| Impedance        |         | 50      |          | $\Omega$ |                    |
| ESD Protection   |         |         | $\pm 8$  | kV       | (Direct discharge) |
|                  |         |         | $\pm 15$ | kV       | (Air discharge)    |

# GPS Active Antenna Module


**APAMP-113**

RoHS/RoHS II compliant  
Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-1)



38.0 X 34.0 X 12mm


## ANTENNA'S IMPEDANCE AND RETURN-LOSS CHARACTERISTICS



S11: Input VSWR

Test condition: 25x25mm ground


## LNA REFLECTION PROFILE



S21: LNA Gain

Test condition: DC 5.0V  
S21=29.04dB

## OUTLINE DRAWING:



| Parameters           | Description        |
|----------------------|--------------------|
| L (Cable Length)     | 250±10cm           |
| Antenna              | Dielectric Ceramic |
| RF Cable             | RG174              |
| RF Cable Attenuation | 1.3dB/m            |
| PCB                  | FR4                |
| RF Connector         | FAKRA-C            |
| Shielding            | Tinplate           |
| Thickness            | 12.8mm             |
| Mounting Type        | Adhesive Tape      |

Unit:mm

ABRACON IS  
ISO9001:2008  
CERTIFIED



Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale **Revised: 10.27.14**  
30332 Esperanza, Rancho Santa Margarita, California 92688  
tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)

# GPS Active Antenna Module

APAMP-113

RoHS/RoHS II compliant  
Lead in copper alloy exemption (6c); and Lead in glass exemption (7c-1)



38.0 X 34.0 X 12mm

## PRODUCT IMAGE:



## PACKAGING:

Each 475 x 215 x 215 mm size carton includes 100 pieces of antenna.



### CAUTION:

- (1) Do not apply excess mechanical stress to the component body or terminations. Do not attempt to re-form or bend the components as this will cause damage to the component.
- (2) Do not expose the component to open flame.
- (3) This specification applies to the functionality of the component as a single unit. Please insure the component is thoroughly evaluated in the application circuit.

**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO9001:2008  
CERTIFIED



Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale **Revised: 10.27.14**  
30332 Esperanza, Rancho Santa Margarita, California 92688  
tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)