


ITEM	PART#	DESCRIPTION	QTY	UOM
A,B	901420006	CGrid Crp Conn Hsg DR FL Polz 6Ckt	2	PC
C	901190109	CGrid Term Fem Crp LFH SnA 2224AWG	12	PC
D	--	PAPER PRINTED PAPER WHITE	1	PC

FROM	TO	DESCRIPTION	COLOR
A1	B5	1X22AWG DISC MPPE BK UL11028	BLACK
A2	B6	1X22AWG DISC MPPE BK UL11028	BLACK
A3	B3	1X22AWG DISC MPPE BK UL11028	BLACK
A4	B4	1X22AWG DISC MPPE BK UL11028	BLACK
A5	B1	1X22AWG DISC MPPE BK UL11028	BLACK
A6	B2	1X22AWG DISC MPPE BK UL11028	BLACK

MOLEX P/N
MOLEX
BATCH WK/YR

DETAIL A

TABLE			
PART NUMBER	L1	L2 (REF)	TITLE
2196581062	150±8	15	CGRID III R-R 6ckt 150mm disc Sn
2196581063	300±10	15	CGRID III R-R 6ckt 300mm disc Sn
2196581064	600±10	15	CGRID III R-R 6ckt 600mm disc Sn



NOTES

1. Cable assembly must pass 100% continuity and polarity test.
2. Connector view shown is from mating side.
3. Label text must be 2mm max. in height with Arial font.
4. Label must be wrapped in Flag type on a single cable.

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2021/12/27	A	INITIAL RELEASE	SAIKIG

DOCUMENT STATUS	P1	RELEASE DATE	2022/01/13	11:15:18
-----------------	----	--------------	------------	----------

FUNCTIONAL SYMBOLS FA = 0 FE = 0 FP = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		<p>SEE TABLE</p> <p>PRODUCT CUSTOMER DRAWING</p>
	DIMENSION UNITS	SCALE	EC NO: 690898		
	mm	NTS	DRWN: SAIKIG 2021/12/27		
	GENERAL TOLERANCES (UNLESS SPECIFIED)		CHK'D: MNARAYAN01 2022/01/13		
ANGULAR TOL ± °		APPR: MNARAYAN01 2022/01/13		DOCUMENT NUMBER	
4 PLACES ±		INITIAL REVISION:		2196581062	
3 PLACES ±		DRWN: SAIKIG 2021/12/27		PSD 000 A	
2 PLACES ±		APPR: MNARAYAN01 2022/01/13		MATERIAL NUMBER	
1 PLACE ±		THIRD ANGLE PROJECTION		SEE TABLE	
0 PLACES ±		DRAWING		CUSTOMER	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SERIES		GENERAL MARKET	
		A4-SIZE		SHEET NUMBER	
		219658		1 OF 1	