



TapeCase Ltd.
1982 Lunt Ave, Elk Grove Village, IL 60007
phone: (847) 299-7880
fax: (847) 299-7804
www.tapecase.com
sales@tapecase.com

Conformable Tape Made with Teflon PTFE 204-10

Product Description

This product is a pressure sensitive tape using skived PTFE film with “high temperature” silicone adhesive.

Application Information

This tape is used in electrical applications such as coil wraps, separators, transformer, slot liners, and harness wrapping where good insulation and heat resistant properties are needed. They are also used in mechanical applications requiring high temperature resistance, a low friction surface or a non-stick surface.

Technical Properties

Property	Test Method	Characteristic
Backing Material		PTFE Film
Backing Thickness (in)		0.010
Adhesive System		Silicone
Adhesive Thickness (in)		0.0015
Adhesion (oz/in)	ASTM-D-1000	55
Tensile Strength (lb/in)	ASTM-D-3759	60
Elongation (%)	ASTM-D-3759	300
Dielectric Strength (volts)	ASTM-D-149	20000
Max Operating Temperature (F)		500
Government Specification	MIL-I-23594C, Type 1	Pass

NOTE:

1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.
2. The above values are “Typical Values” which have a nominal range about them and are not intended for specification purposes