



Wimax Monoblock Ceramic Bandpass Filter

ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

Part Number: AM3575B1007



Electrical specifications

Center Frequency: 3575 MHz
Bandwidth: Fo +/- 25 MHz
Input / Output Impedance: 50 Ohms
Passband: 3562.5-3587.5 MHz
Passband Insertion Loss: 2 dB max
Passband Ripple: 0.5 dB max
Passband Return Loss: 18 dB min
Rejection: 30 dB min @ 3375 MHz
Rejection 2: 10 dB min @ 3500 MHz
Rejection 3: 25 dB min @ 3775 MHz
Power Handling: 1 W

Mechanical




Mounting Method: SMT
Dimensions: 10.6 x 6 x 3.9 mm

Environmental

Operating Temperature: -40°C to 85°C
Storage Temperature: -50°C to +90°C

This product is RoHs compliant.

Outline Drawing:



■ : I/O PORT

▨ : GROUND

TOLERANCE UNLESS

OTHERWISE SPECIFIED : ± 0.3

UNITS : mm



Wimax Monoblock Ceramic Bandpass Filter

ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

Part Number: AM3575B1007



Response Plot:

