


SVxx16xx series

16 Amp High Junction Temperature SCRs




Agency Approval

| Agency | Agency File Number |
|--------|--------------------|
| | L Packages: E71639 |

Main Features

| Symbol | Value | Unit |
|-------------------|---------|------|
| $I_{T(RMS)}$ | 16 | A |
| V_{DRM}/V_{RRM} | 600 | V |
| I_{GT} | 6 to 10 | mA |

Schematic Symbol



Description

The SVxx16xx high junction temperature SCR series is ideal for uni-directional switch applications such as phase control in heating, motor speed controls, converters/rectifiers and inrush current controllers.

These SCRs have a low gate current, (IGT) trigger level of 6mA and 10mA maximum at approximately 1.5V for SVxx16x1 and SVxx16x2, respectively.

Features & Benefits

- Halogen free and RoHS compliant
- 150°C maximum junction temperature
- Surge capability up to 225A at 60 Hz half cycle
- High dv/dt performance
- UL Recognized to UL 1557 as an Electrically Isolated Semiconductor Device

Applications

Typical applications include AC Generator (ACG) rectifiers, battery voltage regulators, generic converters and inrush current controller in various AC and DC applications. Additional applications include controls for power tools, home/brown good and white goods appliances.

Internally constructed isolated packages are offered for ease of heat sinking with high isolation voltage.

SVxx16xx series

16 Amp High Junction Temperature SCRs

Absolute Maximum Ratings — Standard SCRs

| Symbol | Parameter | Test Conditions | Value | Unit |
|---------------------|---|---|------------|------------------|
| V_{DSM} / V_{RSM} | Peak non-repetitive blocking voltage | PW=100 μ s | 800 | V |
| $I_{T(RMS)}$ | RMS on-state current | SVxx16Lx $T_C = 110^\circ\text{C}$ | 16 | A |
| | | SVxx16Rx SVxx16Nx $T_C = 135^\circ\text{C}$ | 16 | |
| | | SVxx16Lx SVxx16Rx SVxx16Nx $T_C = 110^\circ\text{C}$ | 10.2 | |
| $I_{T(AV)}$ | Average on-state current | SVxx16Lx $T_C = 110^\circ\text{C}$ | 10.2 | A |
| | | SVxx16Rx SVxx16Nx $T_C = 135^\circ\text{C}$ | 10.2 | |
| | | single half cycle; f = 50Hz; T_J (initial) = 25°C | 188 | |
| I_{TSM} | Peak non-repetitive surge current | single half cycle; f = 60Hz; T_J (initial) = 25°C | 225 | A |
| | | single half cycle; f = 60Hz; T_J (initial) = 25°C | 225 | |
| I^2t | I^2t Value for fusing | $t_p = 8.3$ ms | 210 | A ² s |
| di/dt | Critical rate of rise of on-state current | f = 60 Hz ; $T_J = 150^\circ\text{C}$ | 100 | A/ μ s |
| I_{GM} | Peak gate current | $T_J = 150^\circ\text{C}$ | 4 | A |
| $P_{G(AV)}$ | Average gate power dissipation | $T_J = 150^\circ\text{C}$ | 0.8 | W |
| T_{stg} | Storage temperature range | | -40 to 150 | °C |
| T_J | Operating junction temperature range | | -40 to 150 | °C |

Note: xx=voltage/10, x=sensitivity

Electrical Characteristics ($T_J = 25^\circ\text{C}$, unless otherwise specified)

| Symbol | Test Conditions | | SVxx16x1 | SVxx16x2 | Unit |
|----------|--|------|----------|----------|------------|
| I_{GT} | $V_D = 12\text{V}; R_L = 60 \Omega$ | MIN. | 2 | 5 | mA |
| | | MAX. | 6 | 10 | |
| V_{GT} | | MAX. | 1.5 | 1.5 | V |
| dv/dt | $V_D = 67\% V_{DRM}$; gate open; $T_J = 125^\circ\text{C}$ | MIN. | 400 | 800 | V/ μ s |
| | $V_D = 67\% V_{DRM}$; gate open; $T_J = 150^\circ\text{C}$ | | 200 | 400 | |
| V_{GD} | $V_D = V_{DRM}$ $R_L = 3.3 \text{ k}\Omega$ $T_J = 150^\circ\text{C}$ | MIN. | 0.2 | 0.2 | V |
| I_H | $I_T = 200\text{mA}$ (initial) | MAX. | 22 | 35 | mA |
| t_q | $I_T = 2\text{A}; t_p = 50\mu\text{s}; dv/dt = 5\text{V}/\mu\text{s}; di/dt = -30\text{A}/\mu\text{s}$ | MAX. | 25 | 25 | μ s |
| t_{gt} | $I_G = 2 \times I_{GT}$ $P_W = 15\mu\text{s}$ $I_T = 32\text{A}$ | TYP. | 2.6 | 2.6 | μ s |

Note: xx=voltage/10, x=package

Static Characteristics

| Symbol | Test Conditions | Value | Unit |
|---------------------|---|---------------------------|-------|
| V_{TM} | $I_T = 32\text{A}; t_p = 380 \mu\text{s}$ | MAX. | 1.6 V |
| I_{DRM} / I_{RRM} | $V_{DRM} = V_{RRM}$ | $T_J = 25^\circ\text{C}$ | 10 |
| | | $T_J = 125^\circ\text{C}$ | 1000 |
| | | $T_J = 150^\circ\text{C}$ | 3000 |

Thermal Resistances

| Symbol | Parameter | Value | Unit |
|------------------|-----------------------|----------------------|------|
| $R_{\theta(JC)}$ | Junction to case (AC) | SVxx16Rx SVxx16Nx | 1.0 |
| | | SVxx16Lx | 2.5 |

Note: xx=voltage/10, x=sensitivity

SVxx16xx series

16 Amp High Junction Temperature SCRs

Figure 1:
Normalized DC Gate Trigger Current vs. Junction Temperature




Figure 2:
Normalized DC Gate Trigger Voltage vs. Junction Temperature




Figure 3:
Normalized DC Holding Current vs. Junction Temperature




Figure 4:
On-State Current vs. On-State Voltage (Typical)




Figure 5:
Power Dissipation (Typical) vs. RMS On-State Current





Figure 6:
Maximum Allowable Case Temperature vs. RMS On-State Current



SVxx16xx series

16 Amp High Junction Temperature SCRs

Figure 7:
Maximum Allowable Case Temperature vs. Average On-State Current




Figure 8:
Peak Capacitor Discharge Current




Figure 9:
Peak Capacitor Discharge Current Derating





Figure 10: Surge Peak On-State Current vs. Number of Cycles



SVxx16xx series

16 Amp High Junction Temperature SCRs

Soldering Parameters


| | | |
|--|------------------------------------|-------------------------|
| Reflow Condition | | Pb – Free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (min to max) (t_s) | 60 – 180 secs |
| Average ramp up rate (Liquidus Temp) (T_L) to peak | | 5°C/second max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 5°C/second max |
| Reflow | - Temperature (T_L) (Liquidus) | 217°C |
| | - Time (t_L) | 60 – 150 seconds |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Time within 5°C of actual peak Temperature (t_p) | | 20 – 40 seconds |
| Ramp-down Rate | | 5°C/second max |
| Time 25°C to peak Temperature (T_p) | | 8 minutes Max. |
| Do not exceed | | 280°C |

Physical Specifications

| | |
|------------------------|--|
| Terminal Finish | 100% Matte Tin-plated |
| Body Material | UL Recognized compound meeting flammability rating V-0 |
| Lead Material | Copper Alloy |

Design Considerations

Careful selection of the correct component for the application's operating parameters and environment will go a long way toward extending the operating life of the Thyristor. Good design practice should limit the maximum continuous current through the main terminals to 75% of the component rating. Other ways to ensure long life for a power discrete semiconductor are proper heat sinking and selection of voltage ratings for worst case conditions. Overheating, overvoltage (including dv/dt), and surge currents are the main killers of semiconductors. Correct mounting, soldering, and forming of the leads also help protect against component damage.




Environmental Specifications

| Test | Specifications and Conditions |
|-----------------------------------|---|
| AC Blocking | MIL-STD-750, M-1040, Cond A Applied Peak AC voltage @ 150°C for 1008 hours |
| Temperature Cycling | MIL-STD-750, M-1051, 1000 cycles; -55°C to +150°C; 15-min dwell-time |
| Temperature/Humidity | EIA / JEDEC, JESD22-A101 1008 hours; 160V - DC: 85°C; 85% rel humidity |
| Resistance to Solder Heat | MIL-STD-750 Method 2031 |
| Solderability | ANSI/J-STD-002, category 3, Test A |
| Lead Bend | MIL-STD-750, M-2036 Cond E |
| Moisture Sensitivity Level | Level 1, JEDEC-J-STD-020D |

SVxx16xx series


16 Amp High Junction Temperature SCRs

Dimensions – TO-220AB (L-Package) – Isolated Mounting Tab



| Dimension | Inches | | Millimeters | |
|-----------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.380 | 0.420 | 9.65 | 10.67 |
| B | 0.105 | 0.115 | 2.67 | 2.92 |
| C | 0.230 | 0.250 | 5.84 | 6.35 |
| D | 0.590 | 0.620 | 14.99 | 15.75 |
| E | 0.142 | 0.147 | 3.61 | 3.73 |
| F | 0.110 | 0.130 | 2.79 | 3.30 |
| G | 0.540 | 0.575 | 13.72 | 14.61 |
| H | 0.025 | 0.035 | 0.64 | 0.89 |
| J | 0.195 | 0.205 | 4.95 | 5.21 |
| K | 0.095 | 0.105 | 2.41 | 2.67 |
| L | 0.060 | 0.075 | 1.52 | 1.91 |
| M | 0.085 | 0.095 | 2.16 | 2.41 |
| N | 0.018 | 0.024 | 0.46 | 0.61 |
| O | 0.178 | 0.188 | 4.52 | 4.78 |
| P | 0.045 | 0.060 | 1.14 | 1.52 |
| R | 0.038 | 0.048 | 0.97 | 1.22 |

Dimensions – TO-220AB (R-Package) – Non-Isolated Mounting Tab Common with Center Lead




| Dimension | Inches | | Millimeters | |
|-----------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.380 | 0.420 | 9.65 | 10.67 |
| B | 0.105 | 0.115 | 2.67 | 2.92 |
| C | 0.230 | 0.250 | 5.84 | 6.35 |
| D | 0.590 | 0.620 | 14.99 | 15.75 |
| E | 0.142 | 0.147 | 3.61 | 3.73 |
| F | 0.110 | 0.130 | 2.79 | 3.30 |
| G | 0.540 | 0.575 | 13.72 | 14.61 |
| H | 0.025 | 0.035 | 0.64 | 0.89 |
| J | 0.195 | 0.205 | 4.95 | 5.21 |
| K | 0.095 | 0.105 | 2.41 | 2.67 |
| L | 0.060 | 0.075 | 1.52 | 1.91 |
| M | 0.085 | 0.095 | 2.16 | 2.41 |
| N | 0.018 | 0.024 | 0.46 | 0.61 |
| O | 0.178 | 0.188 | 4.52 | 4.78 |
| P | 0.045 | 0.060 | 1.14 | 1.52 |
| R | 0.038 | 0.048 | 0.97 | 1.22 |

SVxx16xx series

16 Amp High Junction Temperature SCRs

Dimensions – TO- 263AB (N-package) – D2-Pak Surface Mount



| Dimension | Inches | | Millimeters | |
|-----------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.360 | 0.370 | 9.14 | 9.40 |
| B | 0.380 | 0.420 | 9.65 | 10.67 |
| C | 0.178 | 0.188 | 4.52 | 4.78 |
| D | 0.025 | 0.035 | 0.64 | 0.89 |
| E | 0.045 | 0.060 | 1.14 | 1.52 |
| F | 0.060 | 0.075 | 1.52 | 1.91 |
| G | 0.095 | 0.105 | 2.41 | 2.67 |
| H | 0.092 | 0.102 | 2.34 | 2.59 |
| J | 0.018 | 0.024 | 0.46 | 0.61 |
| K | 0.090 | 0.110 | 2.29 | 2.79 |
| S | 0.590 | 0.625 | 14.99 | 15.88 |
| V | 0.035 | 0.045 | 0.89 | 1.14 |
| U | 0.002 | 0.010 | 0.05 | 0.25 |
| W | 0.040 | 0.070 | 1.02 | 1.78 |

Product Selector

| Part Number | Voltage | Gate Sensitivity | Type | Package |
|-------------|---------|------------------|--------------|---------|
| | 600V | | | |
| SVxx16L1 | X | 6mA | Standard SCR | TO-220L |
| SVxx16R1 | X | 6mA | Standard SCR | TO-220R |
| SVxx16N1 | X | 6mA | Standard SCR | TO-263 |
| SVxx16L2 | X | 10mA | Standard SCR | TO-220L |
| SVxx16R2 | X | 10mA | Standard SCR | TO-220R |
| SVxx16N2 | X | 10mA | Standard SCR | TO-263 |

Note: xx = Voltage/10

Packing Options


| Part Number | Marking | Weight | Packing Mode | Base Quantity |
|-------------|----------|--------|------------------|--------------------|
| SVxx16LxTP | SVxx16Ly | 2.2g | Tube | 1000 (50 per tube) |
| SVxx16RxTP | SVxx16Ry | 2.2g | Tube | 1000 (50 per tube) |
| SVxx16NxTP | SVxx16Ny | 1.6g | Tube | 1000 (50 per tube) |
| SVxx16NxRP | SVxx16Ny | 1.6g | Embossed Carrier | 500 |

Note: xx=voltage/10, x=sensitivity

SVxx16xx series


16 Amp High Junction Temperature SCRs

Part Numbering System



Part Marking System


T0-220 AB - (L and R Package)
T0-263 AB - (N Package)



Date Code Marking
Y: Year Code
M: Month Code
XXX: Lot Trace Code

TO-263 Embossed Carrier Reel Pack (RP) Specifications

Meets all EIA-481-2 Standards



Dimensions are in inches (and millimeters).

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.