


- Material**
- Terminal body (contact pin): Brass(CuZn) Tin plated
 - Insulator (housing): Thermoplastic (UL94V-0) Green
- Electrical cULus**
- Voltage rating: 300VAC
 - Current rating: 20A
 - Wire range:
 - Solid wire(AWG):
 - Stranded wire(AWG):
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -30°C to +105°C
 - Soldering temperature: 245°C ±10°C/5 Sec
 - Safety Approval: () pending

N=Number of contacts

RoHS compliant



File No.: E349947

Scale	1:1
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

①	Id.	Modification	Date	Name
②	Drawn		19.04.2016	Winnie
③	Drawn	Add the UL File No.	10.12.2009	Dean

Date	Name
10.12.2009	Dean
19.04.2016	Winnie

Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace
	A-TB750-00XXCV	ASS 3943 CO	rev02
			Sheet



1	2	3	4	5	6	7
1	2	3	4	5	6	7
H	G	F	E	D	C	B
H	G	F	E	D	C	B