



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours

| Connector dimension |                 |
|---------------------|-----------------|
| Dim                 | Nominal         |
| A                   | 44.5±0.3        |
| B                   | 30.15+0.1/-0.15 |
| R                   | 32.5Max         |
| S                   | 41.3±0.4        |
| W                   | 2.2+0.9/-0.1    |
| VV THREAD           | M25x1-6g        |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D717S08SN**

|              |            |                          |                         |
|--------------|------------|--------------------------|-------------------------|
| A            | 30-09-2016 | First Release            |                         |
| ISS          | DATE       | Latest modification - by | MOD N°                  |
| Designed By: |            | Date:                    | <b>CUSTOMER DRAWING</b> |

|              |                                      |                                |                               |
|--------------|--------------------------------------|--------------------------------|-------------------------------|
| <b>TITLE</b> | Stainless Steel Receptacle 8D series |                                |                               |
| SCALE        | NA                                   | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b> |

|                |                        |   |
|----------------|------------------------|---|
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b> | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|

|                     |  |              |
|---------------------|--|--------------|
| FORMAT<br><b>A3</b> | <b>SOURIAU DRG N°<br/>8D717S08SN-C</b> | SHEET<br>1/2 |
|---------------------|--|--------------|

|               |                                    |   |   |    |   |    |   |   |                 |
|---------------|------------------------------------|---|---|----|---|----|---|---|-----------------|
| BASIC SERIES: | 8D                                 | 7 | - | 17 | S | 08 | S | N | ORIENTATION : N |
| SHELL TYPE    | : Jam nut Receptacle               |   |   |    |   |    |   |   |                 |
| CONTACT TYPE  | : Standard Crimp Contact           |   |   |    |   |    |   |   |                 |
| SHELL SIZE    | : 17                               |   |   |    |   |    |   |   |                 |
| PLATING       | : S = Nickel                       |   |   |    |   |    |   |   |                 |
|               | CONTACT TYPE : SOCKET(500 Matings) |   |   |    |   |    |   |   |                 |
|               | CONTACT LAYOUT : 17-08             |   |   |    |   |    |   |   |                 |

Contact Layout



| Contacts<br>(Insert arrangement 17-8) |             |             |
|---------------------------------------|-------------|-------------|
| Contact position ID                   | Location    |             |
|                                       | X-axis (mm) | Y-axis (mm) |
| A                                     | +000 (0.00) | +236 (5.99) |
| B                                     | +128 (3.25) | +086 (2.18) |
| C                                     | +230 (5.84) | -078 (1.98) |
| D                                     | +094 (2.39) | -216 (5.49) |
| E                                     | -094 (2.39) | -216 (5.49) |
| F                                     | -230 (5.84) | -078 (1.98) |
| G                                     | -128 (3.25) | +086 (2.18) |
| H                                     | +000 (0.00) | -052 (1.32) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 17         | -8              | 8                  | 16            | II             | All              | MS20053-8  |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal       |
|-----|---------------|
| B   | 30.73+0/-0.25 |
| ØC  | 32.01+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D717S08SN

|                     |   |                                |  |
|---------------------|---|--------------------------------|--|
| A                   | 30-09-2016                                  | First Release                  |  |
| ISS                 | DATE  | Latest modification - by       | MOD N°   |
| Designed By:        |   | Date:                          | <b>CUSTOMER DRAWING</b>  |
| <b>TITLE</b>        | <b>Stainless Steel Receptacle 8D series</b> |                                |  |
| SCALE               |   | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>  |
| <b>SOURIAU</b>      | <b>WWW.SOURIAU.COM</b>                      |                                | This document is the property of SOURIAU<br>it must not be reproduced or communicated without permission |
| FORMAT<br><b>A3</b> | <b>SOURIAU DRG N°<br/>8D717S08SN-C</b>      |                                | SHEET<br>2/2   |