


Steward



CORE DIMENSIONS				28T0100-30P	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	2.54	(.100)	±	.13	(.005)
ID	1.27	(.050)	±	.13	(.005)
TH	.99	(.039)	±	.13	(.005)
SINGLE PARYLENE COATING				28T0100-30P	
OD	2.57	(.101)	±	.13	(.005)
ID	1.24	(.049)	±	.13	(.005)
TH	1.02	(.040)	±	.13	(.005)

WEIGHT / K 0.04 LBS
 INITIAL PERMEABILITY 850

ELECTRICAL SPECIFICATION								
	MIN		NOM	MAX	MAX	FREQ.	VOLT.	
	(μH)	MIN TOL.	(μH)	(μH)	TOL.	(kHz)	(V)	URNS
L	0.093	(-20%)	0.117	.140	(+20%)	100	≤ .00027	1
Q	REF	-	-	-	-	100	≤ .00027	1
Net Impedance	MIN		NOM			FREQ.		
	(Ω)	TOL	(Ω)			(MHz)		URNS
Z1 (Ref.)	3.69	(-25%)	4.92	-	-	25	-	1
Z2	6.97	(-25%)	9.29	-	-	150	-	1

COATING SPECIFICATIONS			
	TYPE	Max. Coating (mils.)	Min. DLB VAC TEST FORCE (LB)
	PARYLENE	0.5	1000 0.06

NOTES:



Rev	Description	Date	INT
A	Original Draft	12/18/1997	IS
B	REVISED GAUSS LEVEL TO 10	12/17/2003	TPM
C	RE-ACTIVATE PRINT REMOVE Q SPEC CHANGE P/N	9/28/2005	JRK
D	Revised Template	6/1/2006	WMM

Date: 6/1/2006	DWG # 28T0100-30P-D	Rev:
Drawn By: WMM	Title # 28T0100-30P	D

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT