ATGBICS FTLF8528P2BNV Finisar Compatible Transceiver SFP+ 1.063/2.125/4.25GBase-SR (850nm, MMF, 300m, DOM, Ext Temp)

Brand : ATGBICS

Product code: FTLF8528P2BNV-C

Product name : FTLF8528P2BNV Finisar Compatible Transceiver SFP+ 1.063/2.125/4.25GBase-SR (850nm, MMF, 300m, DOM, Ext Temp)

FTLF8528P2BNV Finisar Compatible Transceiver SFP+ 1.063/2.125/4.25GBase-SR (850nm, MMF, 300m, DOM, Ext Temp)

ATGBICS FTLF8528P2BNV Finisar Compatible Transceiver SFP+ 1.063/2.125/4.25GBase-SR (850nm, MMF, 300m, DOM, Ext Temp):

ATGBICS FTLF8528P2BNV 1.063/2.125/4.25GBase-SR supports a distance of up to 300m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLF8528P2BNV= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported	Fiber optic 4250 Mbit/s SFP+ X V LC SR 300 m 850 nm V	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Digital Diagnostics Monitoring		Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 °C 85 °C -5 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring (DDM)		Weight & dimensions	
Wavelength-division multiplexing (WDM)	×	Width Depth	13.4 mm 56.5 mm
Features		Height	8.5 mm
Product colour	Silver	Weight	19 g
Housing material	Metal	Packaging data	
Plug and Play Hot-Plug support Hot-swap		Number of products included Package type	1 pc(s) Box
Easy to install	1	Technical details	
Country of origin Brand compatibility Certification	China Finisar CE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468761095

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.