


F5DEF3330AAS2K

Aliases (5DEF3330AAS2K)

Obsolete

F5D, Film, Metallized Polyester, Capacitor/Capacitor, 0.33 uF, 10%, 100 VDC, 100°C, Lead Spacing = 10mm

FRONT VIEW



Click [here](#) for the 3D model.

Dimensions

L 13.35mm MAX
H 11.1mm MAX
T 5.2mm MAX
S 10mm +/-0.4mm
LL 4mm +2mm
F 0.75mm +/-0.05mm
G 0.5mm NOM

Packaging Specifications

Packaging Bulk, Bag
Packaging Quantity 1300

General Information

Series F5D
Dielectric Metallized Polyester
Style Radial
Features EMI-RFI suppressors for DC motors
RoHS Yes
Lead Wire Leads
AEC-Q200 No
Miscellaneous The Rated Voltage Decreases 2%/C Between +100C And +125C.
CeramicCapValue= 0.1 uF.

Specifications

Capacitance 0.33 uF
Capacitance Tolerance 10%
Voltage DC 100 VDC, 50 VDC (125C)
Temperature Range -55/+125°C
Rated Temperature 100°C
Dissipation Factor 2.5% 1kHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - b96b2030-1bde-4e88-a4ce-75f019f0c3c3

© 2006 - 2023 KEMET

Generated 5/18/2023 - b96b2030-1bde-4e88-a4ce-75f019f0c3c3

© 2006 - 2023 KEMET