

## Specification Sheet

Part Number: RT250S0UVX2



Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg

Article Number	115-41803
Type	RT250S
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Special extended-pawl design offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li><li>• Buckle feature on head allows excess strap to be tucked away after installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Releasable Cable Tie, Release Tab, 9.1" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg
<b>Global Part Name</b>	RT250S-PA66UV-BK
<b>Minimum Tensile Strength (Imperial)</b>	250.0
<b>Minimum Tensile Strength (Metric)</b>	1115.0
<b>Length L (Imperial)</b>	9.1
<b>Length L (Metric)</b>	230.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.49
<b>Width W (Metric)</b>	12.5
<b>Bundle Diameter Min (Imperial)</b>	0.47
<b>Bundle Diameter Min (Metric)</b>	12.0
<b>Bundle Diameter Max (Imperial)</b>	2.0
<b>Bundle Diameter Max (Metric)</b>	50.0

<b>Thickness T (Imperial)</b>	0.075
<b>Thickness T (Metric)</b>	1.9
<b>Cable Tie Head Length (Imperial)</b>	0.88
<b>Cable Tie Head Width (Imperial)</b>	0.79
<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Material Shortcut</b>	PA66UV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.