



Disconnect Terminals

DKT 4



Lever & Feed Through

DKT 4 V



Dual Level

Terminal Block Selection Data

Available Options	Version	DKT 4		DKT 4 V	
With 2 StB test points KrS PA Beige PA					
		0327860000	0327960000	1304860000	1304960000
		0687360000	0687460000		

Dimensions

Width / Length / Height mm (in.)	for TS 32	6/65/70 (.23/2.56/2.76)	6/65/56.5/70 (.23/2.56/2.76)
	for TS 35	6/65/70 (.23/2.56/2.76)	6/65/56.5/70 (.23/2.56/2.76)
Insulation stripping length	mm (in.)	9 (.35)	9 (.35)

Technical Data

Rated voltage / rated current / wire size	UL	300 V / 10 A / #22...12 AWG	300 V / 10 A / #22...12 AWG
	CSA	300 V / 10 A / #26...12 AWG	300 V / 10 A / #26...12 AWG
	VDE	380 VAC / 10 A / 4 mm ²	380 VAC / 10 A / 4 mm ²
Torque	Nm (lb. in.)	0.6 / 0.5 StB (8.0 / 4.5 StB)	0.6 / 0.5 StB (8.0 / 4.5 StB)
Clamping screw	M	3	3

Selected Accessory Data[‡]

End Plate (thickness mm)	Type	Part No.	Type	Part No.
Beige PA	AP (1.5)	0687560000	AP (1.5)	0687560000
Blue PA				
KrG				
KrS				

Partition (thickness mm)

PA				
KrG				
KrS				
HP	TW (2.0)	0607000000	TW (2.0)	0607000000

Jumpers



Final number indicates number of poles. See the Accessories Section for more information. When using QB, maximum conductor connection is 2.5 mm².

Connection sleeve	QB 2	0482700000	QB 2	0482700000
Fixing screw	QB 3	0482800000	QB 3	0482800000
Lock washer	QB 4	0482900000	QB 4	0482900000
Insulation sleeve	QB 75 bare*	0526400000	QB 75 bare*	0526400000
IP 75	0526700000	IP 75	0526700000	

Plugs

Lock-out device	WTR/SAKR	9525900000		
Test plug	PS 2.3	0180400000	PS 2.3	0180400000
Socket				
Diode plug without diode				
Diode plug with diode 1N4007				
Disconnecter plug (spare)				

Marking Tags

Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50.	Print	DKT 4	DKT 4 V
Consecutive horizontal		DEK 5/6 0468660001	DEK 5/6 0468660001
Consecutive vertical		DEK 5/6 0468760001	DEK 5/6 0468760001

[‡]See Accessories section for additional information.
*Without DLS