



11	ID LABEL	POLYPROPYLENE	CLEAR, (LABEL DETAIL)
10	OVERMOLD	TPE	SEE P/N CHART
9	SOCKET CONTACT	Cu ALLOY	GOLD PLATED
8	WIRE, 18AWG (UL1015)	PVC INSULATION	SEE FACE VIEWS
7	FEMALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
6	FRICITION RING	NYLON	WHITE
5	FEMALE INSERT	TPE	SEE P/N CHART
4	MALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
3	M/F CONTACT (GROUND)	Cu ALLOY	GOLD PLATED
2	M/F CONTACT (SIGNAL)	Cu ALLOY	GOLD PLATED
1	MALE INSERT	TPE	SEE P/N CHART
ITEM	DESCRIPTION	MATERIAL	FINISH

(A) NOTES:
 1. MATERIAL: AS NOTED
 2. FINISH: AS NOTED
 3. ELECTRICAL:
 VOLTAGE: 483V PER IEC60664
 600V PER UL2238
 CURRENT: 10A
 4. TEMP RATING: -20°C TO +80°C
 5. PROTECTION: IP67 (WHEN MATED)
 6. COUPLING THREADS: 7/8-16UN
 7. UL LISTED FILE: E152210
 8. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

1300350115	DNETAUXPTG	BLACK	WHITE
1300350085	DNETAUXPT	YELLOW	BLACK
PART NO.	ENG. NO.	O-MOLD & INSERT COLOR	LABEL PRINT COLOR

FUNCTIONAL SYMBOLS FA=0 FE=0 FP=0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	CURRENT REV DESC: REDRAW TO NX, ADD BOM TABLE, UPDATE NOTES, REMOVE CENEL, ORIENT VIEWS TO MATCH MFG DOC			
	DIMENSION UNITS: INCH SCALE: 2:1 GENERAL TOLERANCES (UNLESS SPECIFIED): 4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ± ANGULAR TOL ± °				
DIVISIONAL SYMBOLS	EC NO: 701309 DRWN: RSTONE CHK'D: MZIELINSKI APPR: BWOODMAN	2022/03/14 2022/03/29 2022/04/11	MINI-CHANGE TEE 4 POLE MALE/FEM TRUNK, 4 POLE FEMALE DROP SINGLE KEY		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	INITIAL REVISION: DRWN: DRWN BY APPR: APPR BY	0099/99/99 0099/99/99	PRODUCT CUSTOMER DRAWING		
THIRD ANGLE PROJECTION	DRAWING C-SIZE	SERIES 130035	DOCUMENT NUMBER 1300350085	DOC TYPE PSD	DOC PART 000
			CUSTOMER	REVISION A	SHEET NUMBER 1 OF 1