

product type designation

product description

Cable 830-1T

Plug-in cable, preferred length, preassembled with two 9-pole D-sub connectors

Plug-in cable 830-1T for PROFIBUS for connection of terminal devices to OLM and OBT Already pre-assembled with 2 D-sub connectors, 9-pole, cable terminated on both ends, 1.5 m.



suitability for use	For connecting PROFIBUS stations to OLM or OBT
cable designation	L-02YSCY 1x2x0,22 VZN VI
wire length	1.5 m
electrical data	
number of electrical connections	2
insulation resistance coefficient	1 GΩ·m
capacity per length / at 1 kHz	30 pF/m
operating voltage	
• RMS value	80 V
mechanical data	
number of electrical cores	2
design of the shield	Braided shield made of tin-plated copper wires
outer diameter	
• of inner conductor	0.61 mm
• of the wire insulation	1.8 mm
• of cable sheath	5.7 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
material	
• of the wire insulation	polyethylene (PE)
• of cable sheath	PVC
color	
• of cable sheath	Violet
bending radius	
• with multiple bends / minimum permissible	86 mm
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
fire behavior	flame resistant according to IEC 60332-1
chemical resistance	
• to mineral oil	oil resistant according to IEC 60811-2-1 (4 h / 70°C)
protection class IP	IP20
product features, product functions, product components / general	
product feature	

<ul style="list-style-type: none"> silicon-free 	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> EAC approval CE marking 	Yes Yes
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) French marine classification society (BV) Det Norske Veritas (DNV) Germanische Lloyd (GL) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) Polski Rejestr Statkow (PRS) 	No No No No No No No
reference code	
<ul style="list-style-type: none"> according to IEC 81346-2 according to IEC 81346-2:2019 	WG WGB
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	12/31/2021 