

GR900 SMD Space, Ceramic, 360 pF, 5%, 200 VDC, BP, N/A, 1210





Click here for the 3D model.

Dimensions	
Chip Size	1210
L	3.07mm +/-0.38mm (0.121 in +/-0.015 in)
W	2.56mm +/-0.38mm (0.101 in +/-0.015 in)
Т	1.6mm MAX (0.063 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Packaging Specifications	
Packaging	Bulk, Bag

GR900 SMD Space
SMD Chip
No
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
4848e250-8508-4d7b-8b2c-b2000a1148f1
Lead (SnPb)
N/A
Mil-PRF-123 Group A
MIL-PRF-123 Group A
No
78 Weeks
1

Specifications			
Capacitance	360 pF		
Capacitance Tolerance	5%		
Voltage DC	200 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	BP		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.