

VIEW ON MATING SIDE

∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
◁	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20

A = 32 CONTACTS L-2,9

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85040-0002 sht.1
Technical Data	PS-85042-0001

A	G2/0	a1-16	b1-16
Contact symbol	Perform. level	Contact position number	

ECN 2264 Produkt spec. 96-10-18 KN	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	LTR	Δ-1		
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2°		DRWG BY	SIGN	
INCH		Ca		
METRIC		CHK'D BY	SIGN	
3 PLACE ± .		KN		
2 PLACE ± .		APP'D BY	SCALE	
1 PLACE ± .				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				
DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.				
EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.				
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY				
REVISE ONLY ON CAD SYSTEM		SH. REV.		
CAD/CAM PROJECT NAME		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
s8504000		s11		
TITLE		SHEET NO. DATE		
32 pos. female connector acc. DIN 41612 style B/2 contacts arrangement		1 OF 1 96/05/15		
MOLEX EUROPE		DWG NO. SDA-85040-0012		
PART NO. 85040-0012		SIZE A		