



## Quartz Crystal Specification

IQD Part No. + Packaging: LFX TAL082542Reel

Würth Part No. 830108254201



### Description

- Quartz crystal in a ceramic package with a electro beam sealed metal lid.
- Model IQXC-240
- Model Issue number 4

### Frequency Parameters

- Frequency 32.0MHz
- Frequency Tolerance  $\pm 7.00$ ppm
- Frequency Stability  $\pm 15.00$ ppm
- Operating Temperature Range -30.00 to 85.00°C
- Overtone Order Fundamental

### Electrical Parameters

- Load Capacitance (CL) 5.00pF
- Drive Level 100 $\mu$ W max
- ESR 100.00 $\Omega$  max

### Environmental Parameters

- Storage Temperature Range: -55 to 125°C

### Compliance

- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

### Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481D  
Pack Size: 5,000
- Alternative packing option available


## USEFUL LINKS

### Toolbox:


[www.we-online.com/toolbox](http://www.we-online.com/toolbox)

### Product Catalog:

[www.we-online.com/products](http://www.we-online.com/products)



### Outline (mm)




### Pad Connections

- Crystal
- GND(Lid)
- Crystal
- N/C

Note: connect pad 2 to GND for correct operation.

### Solder Pad Layout



### CONTACT INFORMATION:

Würth Elektronik eiSos GmbH & Co. KG  
Max-Eyth-Str. 1, 74638 Waldenburg, Germany  
Tel: +49(0) 7942 945-0

Email: [eiSos@we-online.de](mailto:eiSos@we-online.de)  
Web: [www.we-online.com](http://www.we-online.com)